

# ARY rod suspended

canopy trim

049-5121517F 005-3522017 002-90733



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR
cd/m <sup>2</sup>
CRI
1ADDR
X-PERT

## General

Techo , Suspendido
blanco , RAL9016 <sup>1</sup>
Baldaquin blanco tráfico
IP20
791 lm

## LED

3000 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 90 , R <sub>f(1-15)</sub> : 87
MR 0.59
MDER 0.54

## Óptico

flood
beam angle 44°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
11.2 W
CP2 220-240V
71 lm/W
1 DALI Addr.

## Físico

varilla 1500 mm
diameter 47 mm
altura 110 mm
0.65 kg

## Orificio

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 130 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

