

ARY rod suspended

canopy trimless

049-5121517F 005-3512017 002-90732



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR ≤ 16
cd/m² ≤ 1500
CRI ≥ 90
X-PERT

General

Techo , Suspendido
blanco , RAL9016 ¹
Baldaquin blanco tráfico
IP20
791 lm

LED

3000 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 100 , R _f : 90 , R _{f(1-15)} : 87
MR 0.59
MDER 0.54

Óptico

flood
beam angle 44°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
11.2 W
CP2 220-240V
71 lm/W

Físico

varilla 1500 mm
diameter 47 mm
altura 110 mm
0.59 kg

Orificio

diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 70 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

