

SASSO 100 square wallwasher/floor

trimless

048-2750511W 048-2797117 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



General

Techo , Empotrado
negro , RAL9005 ¹
Set de montaje blanco tráfico
IP20
2640 lm

LED

3000 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Óptico

wallwasher floor
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
sistema 27.5 W
inserto 23.4 W
36 Vf
700 mA
CP2 220-240V
sistema 96 lm/W ³
inserto 113 lm/W ⁴

Físico

sin borde
longitud 105 mm
ancho 105 mm
altura 96 mm
0.67 kg

Orificio

longitud 106 mm
ancho 106 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)
⁴ incl. optical losses


Instrucciones de montaje



Calculadora de iluminación



Distribución luminosa



Diseño del producto

