

SASSO 100 square downlight

trimless

048-2710617M 048-2797117 002-90777



Proyecto / Tipo

Notas

Cantidad / Fecha



↑ IP20

↓ IP44

220-240V

X-PERT

UGR

≤ 19

CRI

≥ 90

X-PERT

General

Techo , Empotrado

blanco , RAL9016 ¹

Set de montaje blanco tráfico

parte delantera IP44 , parte trasera IP20

1640 lm

LED

4000 K

IRC ≥ 90

L80 / 50000 h

MacAdam inicial ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Óptico

medium

beam angle 34°

UGR < 19

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Eléctrico

non atenuable

20.2 W

inserto 17.2 W

36 Vf

500 mA

CP2 220-240V

81 lm/W

inserto 95 lm/W

Físico

sin borde

length 105 mm

width 105 mm

altura 75 mm

0.49 kg

Orificio

length 106 mm


width 106 mm

min. ceiling thickness 12.5 mm

max. ceiling thickness 25 mm

recessed depth 80 mm

Distribución luminosa



Diseño del producto

