

SASSO 100 square downlight

trim 2 lamps

048-2710614S 048-279931G 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ P20 ↓ P44	220-240V	X-PERT	UGR ≤ 16	cd/m ² ≤ 3000	CRI ≥ 90	X-PERT	
----------------	----------	--------	-------------	-----------------------------	-------------	--------	--

General

Techo , Empotrado
plata mate
Set de montaje aluminio blanco
parte delantera IP44 , parte trasera IP20
4200 lm

LED

4000 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R _{t(1-15)} : 89
MR 0.81
MDER 0.74

Óptico

spot
ángulo de haz 20°
UGR < 16 , ≥ 65° < 3000 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
58 W
inserto 24.8 W
36 Vf
700 mA
total de insertos 50 W
CP2 220-240V
72 lm/W
inserto 85 lm/W

Físico


borde
longitud 218 mm
ancho 118 mm
altura 75 mm
0.55 kg

Orificio

longitud 210 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

