

SASSO 100 square downlight

trim

048-2710611F 048-2797318 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
negro , RAL9005 ¹
Set de montaje negro intenso
delante IP44 , detrás IP20
2250 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R _{t(1-15)} : 89
MR 0.81
MDER 0.74

Óptico

flood
ángulo de haz 45°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
29.2 W
inserto 24.8 W
36 Vf
700 mA
CP2 220-240V
77 lm/W

Físico


borde
longitud 118 mm
ancho 118 mm
altura 75 mm
0.49 kg

Orificio

longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

