

# SASSO 100 square downlight

trim 2 lamps

048-2710514F 048-279931G 002-90777



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ P20 ↓ P44	220-240V	X-PERT	UGR ≤ 16	cd/m² ≤ 1500	CRI ≥ 90	X-PERT	
----------------	----------	--------	-------------	-----------------	-------------	--------	--

## General

Techo , Empotrado
plata mate
Set de montaje aluminio blanco
parte delantera IP44 , parte trasera IP20
3380 lm

## LED

3000 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 88
MR 0.59
MDER 0.53

## Óptico

flood
ángulo de haz 45°
UGR < 16 , ≥ 65° < 1500 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

non atenuable
40 W
inserto 17.2 W
36 V <sub>f</sub>
500 mA
total de insertos 34 W
CP2 220-240V
85 lm/W
inserto 98 lm/W

## Físico


borde
longitud 218 mm
ancho 118 mm
altura 75 mm
0.57 kg

## Orificio

longitud 210 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

