

# SASSO 100 square downlight

trim

048-2710419S 048-2797317 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Empotrado
dorado , RAL260-M <sup>1</sup>
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1850 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Óptico

spot
ángulo de haz 20°
UGR < 13 , ≥ 65° < 3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

non atenuable
29.2 W
inserto 24.8 W
36 Vf
700 mA
CP2 220-240V
63 lm/W

## Físico


borde
longitud 118 mm
ancho 112 mm
altura 75 mm
0.49 kg

## Orificio

longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

