

SASSO 100 square downlight

trim 2 lamps

048-2710414F 048-2799317 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	UGR ≤16	cd/m² ≤3000	CRI ≥90	X-PERT
------------------	----------	--------	------------	----------------	------------	--------

General

Techo , Empotrado
plata mate
Set de montaje blanco tráfico
parte delantera IP44 , parte trasera IP20
4180 lm

LED

2700 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _r : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Óptico

flood
beam angle 45°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
58 W
inserto 24.8 W
36 Vf
700 mA
total de insertos 50 W
CP2 220-240V
72 lm/W
inserto 84 lm/W

Físico


borde
length 218 mm
width 118 mm
altura 75 mm
0.56 kg

Orificio

length 210 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

