

SASSO 100 square downlight

trim 2 lamps

048-2710414S 048-279931G 002-90777



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



| | | | | | | | |
|----------------|----------|--------|------------|----------------|------------|--------|--|
| ↑ P20 ↓ P44 | 220-240V | X-PERT | UGR ≤13 | cd/m² ≤3000 | CRI ≥90 | X-PERT | |
|----------------|----------|--------|------------|----------------|------------|--------|--|

General

| |
|---|
| Techo , Empotrado |
| plata mate |
| Set de montaje aluminio blanco |
| parte delantera IP44 , parte trasera IP20 |
| 2840 lm |

LED

| |
|---|
| 2700 K |
| IRC ≥ 90 |
| L80 / 50000 h |
| MacAdam inicial ≤ 2 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.53 |
| MDER 0.48 |

Óptico

| |
|-----------------------------|
| spot |
| ángulo de haz 20° |
| UGR < 13 , ≥65° <3000 cd/m² |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Eléctrico

| |
|------------------------|
| non atenuable |
| 40 W |
| inserto 17.2 W |
| 36 V _f |
| 500 mA |
| total de insertos 34 W |
| CP2 220-240V |
| 71 lm/W |
| inserto 83 lm/W |

Físico


| |
|-----------------|
| borde |
| longitud 218 mm |
| ancho 118 mm |
| altura 75 mm |
| 0.57 kg |

Orificio

| |
|------------------------------|
| longitud 210 mm |
| ancho 112 mm |
| espesor mín. del techo 2 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 100 mm |

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

