



STRETTA

surface


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end cap galvanically chromed or in same colour as housing (chromed border); suitable for wall or ceiling mounting; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

ES Perfil de aluminio extrusionado, versión angular; sin tornillos visibles; superficie con recubrimiento de pintura en polvo; perfil de luminaria premontable; tapa terminal en cromado galvanizado o con recubrimiento de polvo en el color de la luminaria (borde cromado); apropiada para montaje en techo y paredes; con proyección de luz por tres lados; tapa HPO (High Performance Opal) para iluminación homogénea; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000K, 4000K
CRI ≥ 90, 3 SDCM
up to 112lm/W
L80 @ 50000h
non DIM, DALI-2
opal cover
IP 44

Types




Luminaire colours



End caps colours




Light distribution



wall
illumination



splash water
protection (IP 44)



CRI ≥ 98
XPECTRUM

Order options


COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
non DIM	1
DALI-2	3

MATERIAL COLOUR	
○ pure white RAL 9010*	7
○ pure white/☉ chrome**	C
● jet black RAL 9005*	8

*end caps in housing colour with chromed boarder

**end caps completely in chrome




LIGHT OPTIC COVER

opal high performance


Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM




STRETTA surface



LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13W	3000K	1370lm	600	057-0132::H
	4000K	1460lm		
19.5W	3000K	2050lm	900	057-0133::H
	4000K	2190lm		
26.1W	3000K	2740lm	1200	057-0134::H
	4000K	2920lm		

Light distribution



opal high performance

LUMINOUS FLUX value calculated for
CRI ≥ 90, colour white, cover opal