



## SASSO 100 round

recessed

**EN** Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

**ES** Proyector empotrable redondo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; elección de la característica de radiación; ajustable o fija simétrica o asimétrica; variantes de radiación simétrica: proyección precisa con óptica de lente de alta calidad; variantes con emisión asimétrica: reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; Chip on Board que proporciona una máxima eficiencia (ADJUSTABLE y DOWNLIGHT); no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,  
CWD 1800–3000K  
CRI ≥ 90, 2 SDCM  
up to 122lm/W  
L80 @ 50000h  
non DIM, DALI-2  
↓ IP44/↑ IP20

### Types



### Housing colours



### Inset colours



### Light distributions



rotatable 360°,  
tiltable 30°



wallwasher and  
ww floor inset



glare control  
(UGR ≤ 16)



80 mm  
recess depth



CWD  
1800–3000K



CRI ≥ 95  
2 SDCM



## Electrical accessories

### SASSO 100

**POWER SUPPLY** 220-240 V AC, 50-60Hz,  PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA   non DIM	$\eta$ 88 %	143-43-30	002-90766
450 mA   DALI-2	$\eta$ 88 %	143-43-30	002-90767
650 mA   non DIM	$\eta$ 88 %	143-43-30	002-90780
650 mA   DALI-2	$\eta$ 88 %	143-43-30	002-90789
700 mA   non DIM	$\eta$ 80 %	143-43-30	002-90774
700 mA   DALI-2	$\eta$ 88 %	143-43-30	002-90776

### THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable $\varnothing$ 4-12mm	105-58-30	005-2531110
DALI cable $\varnothing$ 4-12mm	105-58-30	005-2551110

### DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W   48V DC constant voltage	72-90-63	005-6520210
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2 x 42W   48V DC   U <sub>OUT</sub> 10-40V	36-88-59	005-6121030

for more details and components see catalog XAL 22, page 981