

SASSO 100 square downlight

trimless

048-2710E11W 048-2797117 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	X-PERT	UGR ≤22	CRI ≥90	1ADDR	X-PERT
------------------	----------	--------	------------	------------	-------	--------

General

Techo , Empotrado
negro , RAL9005 ¹
Set de montaje blanco tráfico
parte delantera IP40 , parte trasera IP20
2100 lm

LED

colour warm dimming
1800 K - 3000 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 100 , R _f : 89 , R _{f(1-5)} : 89
MR 0.56
MDER 0.51

Óptico

wide flood
beam angle 51°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

DALI-2
28.0 W
inserto 23.8 W
700 mA
CP2 220-240V
75 lm/W
inserto 88 lm/W
1 DALI Addr.

Físico


sin borde
length 105 mm
width 105 mm
altura 75 mm
0.51 kg

Orificio

length 106 mm
width 106 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

