

# SPIO 20 downlight

trimless

048-1710510W 048-1698107 002-90784



Proyecto / Tipo

Notas

Cantidad / Fecha



## General

Techo , Empotrado

giro 360°

blanco , RAL9016 <sup>1</sup>

blanco tráfico

IP20

435 lm

## LED

3000 K

IRC  $\geq$  90

L85 / 50000 h

MacAdam inicial  $\leq$  3 SDCM

R<sub>g</sub>: 104 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 92

MR 0.59

MDER 0.54

## Óptico

wide flood

ángulo de haz 44°

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Eléctrico

DALI-2

sistema 8.7 W

inserto 6.5 W

12 Vf

600 mA

CP2 220-240V

sistema 50 lm/W<sup>3</sup>

inserto 66 lm/W<sup>4</sup>

1 DALI Addr.

## Físico

sin borde

diámetro 26 mm

altura 66 mm

## Orificio

diámetro 48 mm

espesor mín. del techo 9 mm

espesor máx. del techo 25 mm

profundidad empotrada 80 mm


<sup>1</sup> Código RAL

<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>4</sup> incl. optical losses

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

