



MOVE IT 10 system

recessed trimless/surface


EN Thin extruded aluminium profile with 16 mm (trimless) or 11 mm (surface) height and 10 mm width groove; optionally for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5 mm ceiling thickness; MOVE IT 10 trimless profile with processing protection against penetration of filler; or for wall-/ceiling surface mounting; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of FLEX or LEVEL connectors; with integrated power track profile for take off of supply voltage and DALI-2 signal; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

ES Perfil bajo de aluminio extruido con 16 mm (trimless) o 11 mm (surface) de altura y 10 mm de anchura de junta; disponible para el encastre sin bordes en techos de cartón yeso (montaje en pared o techo) de 12,5 mm de espesor; perfil MOVE IT 10 trimless con protección contra la penetración de masilla; o para montaje sobre pared/techo; diseñado para la creación de sistemas continuos; montaje flexible del sistema con conectores en forma de L, T o X y conectores FLEX o LEVEL; con perfil de raíl electrificado integrado para la recepción de la tensión de alimentación y DALI-2; superficie anodizada o recubierto de polvo; montaje flexible y sin herramienta de los insertos con cierre de clip



Quickinfo

2700K, 3000K, 4000K
CRI ≥ 90
L90 @ 50 000h
DALI-2


Types



Configurations



Colours



custom cut on building site

Order options

CONTROL

DALI-2

MATERIAL COLOUR

- traffic white 9016 / jet black 9005 P 8
- jet black RAL 9005 8

MATERIAL COLOUR

ACCESSORIES

- traffic white* RAL 9016 7
- jet black RAL 9005 8



*mechanical connectors are always traffic white / jet black accept mechanical recessed trimless

Options on request

CONNECTOR

- T connector mechanical
 - X connector mechanical
- only for recessed trimless

MOVE IT 10 trimless





INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-1113038
2100	channel	030-1115038
3100	channel	030-1117038
custom cut	channel	E83610 8



END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-1120018
linear connector electrical	030-2101138
L connector electrical	030-2111138
T connector electrical*	030-2121138
X connector electrical*	030-2131138
linear connector mechanical	030-1134018
L connector mechanical	030-1135018

*when using T and X connector mechanical more electrical and mechanical connectors see p. 19



MOVE IT 10 surface






INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-121303 <input checked="" type="checkbox"/>
2100	channel	030-121503 <input checked="" type="checkbox"/>
3100	channel	030-121703 <input checked="" type="checkbox"/>
custom cut	channel	E83620 <input checked="" type="checkbox"/>
R 300	curve channel	030-123103 <input checked="" type="checkbox"/>
R 500	curve channel	030-123203 <input checked="" type="checkbox"/>

END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-122001 <input checked="" type="checkbox"/>
linear connector electrical	030-2101138
L connector electrical	030-2111138
T connector electrical	030-2121138
X connector electrical	030-2131138
linear connector mechanical	030-123401 <input checked="" type="checkbox"/>
L connector mechanical	030-123501 <input checked="" type="checkbox"/>
T connector mechanical	030-123601 <input checked="" type="checkbox"/>
X connector mechanical	030-123701 <input checked="" type="checkbox"/>

more electrical and mechanical connectors see p. 19



Accessories

BLIND COVER

L (mm)		ORDER CODE
1100	blind cover	030-100301 <input checked="" type="checkbox"/>
2100	blind cover	030-100501 <input checked="" type="checkbox"/>
3100	blind cover	030-100701 <input checked="" type="checkbox"/>
custom cut	blind cover	E83600 <input checked="" type="checkbox"/>




ELECTRICAL ACCESSORIES

TYPE	ORDER CODE
power feeder (only for surface)	030-2523038
internal power feeder (incl. cable 2000 mm)	030-2525038

MOUNTING ACCESSORY

TYPE	ORDER CODE
3-in-1 mounting tool	030-2611000

guiding device for custom cut on building site (2 pcs required); drilling template for Indirect Light Inset and Pass Through Connector





MOVE IT 10 system

suspended


EN Thin extruded aluminium profile with 10 mm width groove; choice of angular (24 mm height) or tubular (26 mm height) design; for suspended mounting (cable suspension, height adjustment without tools, incl. black feed); with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of PASS THROUGH connector; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of LEVEL connectors; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

ES Perfil bajo de aluminio extruido con 10 mm de anchura de junta; disponible en forma angular (24 mm de altura) o tubular (26 mm de altura); para montaje suspendido (suspensión por cable, ajuste de altura sin herramienta, cable de alimentación negro incluido); con perfil de carril electrificado incorporado en ambos lados para la toma de suministro eléctrico y señal DALI-2; suministro eléctrico y señal DALI-2 para ambos carriles electrificados con una sola toma de alimentación mediante conector PASS THROUGH; diseñado para la creación de sistemas continuos; montaje flexible del sistema con conectores en forma de L, T o X y conectores LEVEL; superficie anodizada o recubierto de polvo; montaje flexible y sin herramienta de los insertos con cierre de clip


Quickinfo

2700K, 3000K, 4000K
CRI ≥ 90
L90 @ 50 000h
DALI-2


Types



Configurations



Colours



custom cut on building site

Order options

CONTROL

DALI-2

MATERIAL COLOUR

- traffic white 9016 / jet black 9005 P 8
- jet black RAL 9005 8

MATERIAL COLOUR ACCESSORIES


- traffic white* RAL 9016 7
- jet black RAL 9005 8

*mechanical connectors are traffic white / jet black

MATERIAL COLOUR CABLE SUSPENSION

- chrome 4
- jet black RAL 9005 8

MOVE IT 10 square suspended




INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-131303
2100	channel	030-131503
3100	channel	030-131703
custom cut	channel	E83630
R 300	curve channel	030-133103
R 500	curve channel	030-133203


END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-132001
linear connector electrical	030-2101138
L connector electrical	030-2111138
T connector electrical	030-2121138
X connector electrical	030-2131138
linear connector mechanical	030-133401
L connector mechanical	030-133501
T connector mechanical	030-133601
X connector mechanical	030-133701

more electrical and mechanical connectors see page 19



MOVE IT 10 round suspended




INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-141303
2100	channel	030-141503
3100	channel	030-141703
custom cut	channel	E83640
R 300	curve channel	030-143103
R 500	curve channel	030-143203

END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-142001
linear connector electrical	030-2101138
L connector electrical	030-2111138
T connector electrical	030-2121138
X connector electrical	030-2131138
linear connector mechanical	030-143401
L connector mechanical	030-143501
T connector mechanical	030-143601
X connector mechanical	030-143701

more electrical and mechanical connectors see page 19



Accessories

BLIND COVER see page 17


INDIRECT LIGHT INSET see page 17

CABLE SUSPENSION / CANOPY / ELECTRICAL ACCESSORIES

TYPE	L (mm)	ORDER CODE
cable suspension	1500	030-223001
cable susp. linear connector	1500	030-221001
cable susp. linear conn. electrical	1500	030-222001
canopy square	90-90-22	005-231171
canopy round	ø90-22	005-260073
internal power feeder (incl. cable 2000mm)		030-2525038
pass through connector electrical (pair)		030-2171138
3-in-1 mounting tool*		030-2611000

*guiding device for custom cut on building site (2 pcs required); drilling template for Indirect Light Inset and Pass Through Connector

more electrical and mechanical connectors see page 19





MOVE IT 10 system

pole


EN Thin extruded aluminium profile with 10 mm width groove; choice of angular (24 mm height) or tubular (26 mm height) design; for vertical and horizontal mounting; easy installation of the mounting set, incl. feed; with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of PASS THROUGH connector; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of LEVEL connectors; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

ES Perfil bajo de aluminio extruido con 10 mm de anchura de junta; disponible en forma angular (24 mm de altura) o tubular (26 mm de altura); para montaje en vertical y en horizontal; instalación sencilla del kit de montaje, incl. toma de alimentación; con perfil de carril electrificado incorporado en ambos lados para la toma de suministro eléctrico y señal DALI-2; suministro eléctrico y señal DALI-2 para ambos carriles electrificados con una sola toma de alimentación mediante conector PASS THROUGH; diseñado para la creación de sistemas continuos; montaje flexible del sistema con conectores en forma de L, T o X y conectores LEVEL; superficie anodizada o recubierto de polvo; montaje flexible y sin herramienta de los insertos con cierre de clip


Quickinfo

2700K, 3000K, 4000K
CRI ≥ 90
L90 @ 50 000h
DALI-2


Types



Mounting types



Colours



custom cut on building site

Order options

COLOUR TEMPERATURE	
2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR	
● traffic white 9016 / jet black 9005 P	8
● jet black RAL 9005	8

MATERIAL COLOUR	
○ traffic white* RAL 9016	7
● jet black RAL 9005	8

*mechanical connectors are traffic white/jet black

MOVE IT 10 square pole



INSTALLATION TRACK


L (mm)		ORDER CODE
1100	channel	030-131303
2100	channel	030-131503
3100	channel	030-131703
custom cut	channel	E83630

MOUNTING SET



TYPE	ORDER CODE
floor to ceiling set (pair)	030-134101
wall to wall set (pair)	030-134101
floor to wall set (wall bracket 400 mm incl. end cap)	030-134201
ceiling set (incl. end cap)	030-134301

MOVE IT 10 round pole



INSTALLATION TRACK


L (mm)		ORDER CODE
1100	channel	030-141303
2100	channel	030-141503
3100	channel	030-141703
custom cut	channel	E83640

MOUNTING SET



TYPE	ORDER CODE
floor to ceiling set (pair)	030-144101
wall to wall set (pair)	030-144101
floor to wall set (wall bracket 400 mm incl. end cap)	030-144201
ceiling set (incl. end cap)	030-144301

LIGHT INSET 10



INDIRECT incl. feeder


INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
15.8 W	2700 K	1080 lm	1000	030-6330
	3000 K	1140 lm		
	4000 K	1190 lm		
32 W	2700 K	2170 lm	2000	030-6370
	3000 K	2280 lm		
	4000 K	2390 lm		

Accessories

BLIND COVER


L (mm)		ORDER CODE
1100	blind cover	030-100301
2100	blind cover	030-100501
3100	blind cover	030-100701
custom cut	blind cover	E83600

ELECTRICAL ACCESSORIES



TYPE	ORDER CODE
internal power feeder (incl. cable 2000 mm)	030-2525038
pass through connector electrical (pair)	030-2171138

MOUNTING ACCESSORY



TYPE	ORDER CODE
3-in-1 mounting tool	030-2611000
guiding device for custom cut on building site (2 pcs required); drilling template for Indirect Light Inset and Pass Through Connector	


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



Types

- 1 Linear Connector
- 2 L-Connector
- 3 T-Connector
- 4 X-Connector
- 5 Flex Connector
- 6 Ceiling to Wall Connector
- 7 Level Connector
- 8 Pass Through Connector

Configurations



Colours



ELECTRICAL accessories

MOVE IT 10 system

EN Mechanical and electrical connectors to MOVE IT 10 system; in L-, T- or X-shape; or FLEX, CEILING TO WALL or LEVEL connectors, as well as PASS THROUGH connectors; for flexible system design; different converters for the entire MOVE IT system

ES Conectores mecánicos y eléctricos para MOVE IT 10 system; en forma de L, T o X; o conectores FLEX, CEILING TO WALL, LEVEL, y PASS THROUGH; para el montaje flexible del sistema; diferentes drivers para todo el sistema MOVE IT

Order options

CONNECTOR MECHANICAL	T
recessed*	1
surface	2
suspended square	3
suspended round	4

*T- and X-connector on request

CONTROL

DALI-2	
--------	--

MATERIAL COLOUR ACCESSORIES

○ traffic white* RAL 9016	7
● jet black RAL 9005	8

*mechanical connectors are always traffic white/jet black accept mechanical recessed trimless

Options on request

CONNECTOR

T connector mechanical	
X connector mechanical	
only for recessed trimless	

Electrical accessories

LINEAR CONNECTOR

TYPE	ORDER CODE
linear connector electrical	030-2101138
linear connector mechanical	030-1T3401■

L CONNECTOR

TYPE	ORDER CODE
L connector electrical	030-2111138
L connector mechanical	030-1T3501■

T CONNECTOR

TYPE	ORDER CODE
T connector electrical	030-2121138
T connector mechanical	030-1T3601■

X CONNECTOR

TYPE	ORDER CODE
X connector electrical	030-2131138
X connector mechanical	030-1T3701■

FLEX/CEILING TO WALL/ LEVEL

TYPE	ORDER CODE
flex connector electrical	030-2141138
ceiling to wall connector electrical	030-2161138
level connector electrical	030-2151138
level connector mechanical	030-2351118

PASS THROUGH CONNECTOR








TYPE	ORDER CODE
pass through connector electrical (pair)	030-2171138
electrical connection from direct to indirect and vice versa	

MOUNTING ACCESSORY

TYPE	ORDER CODE
3-in-1 mounting tool	030-2611000
guiding device for custom cut on building site (2 pcs required); drilling template for Indirect Light Inset and Pass Through Connector	

POWER FEEDER

TYPE	ORDER CODE
power feeder (only for surface)	030-2523038
internal power feeder (incl. cable 2000 mm)	030-2525038




Order options
CONTROL

DALI-2

MATERIAL COLOUR

● jet black RAL 9005

WIRELESS TO DALI-2 control device


POWER SUPPLY EXTERNAL supply 220-240V AC, 48V, 50-60Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
100W	PC II η 92%	external	350-30-18	002-62134
150W	PC II η 92%	external	350-30-18	002-62135
250W	PC II η 93%	external	400-40-22	002-62139

ENEC approved

POWER SUPPLY BASIC 48V


220-240V | 50-60Hz | PC II | Lifetime @ 120W, 45° ambient temp. cascable max. 3 devices

TYPE	EFFICIENCY/LIFETIME	W-H-D (mm)	ORDER CODE
160W	η 94.5% / > 100.000h	72-90-63	005-6520210

DIN RAIL POWER SUPPLY PRO 48V


220-240V | 50-60Hz | PC I | MTBF @ 55° ambient temperature cascable max. 5 devices (240W) or 3 devices (480W)

TYPE	EFFICIENCY/MTBF	W-H-D (mm)	ORDER CODE
240W	η 92% / > 400.000h	60-125-100	005-6220110
480W	η 93% / > 350.000h	120-125-100	005-6220210


DALI-2 SELV DEVICE

TYPE	L-W-H (mm)	ORDER CODE
control unit	213-37-25	050-2061130

necessary to create DALI-2 SELV signal; DALI power supply integrated


WIRELESS TO DALI-2 CONTROL DEVICE

TYPE	L-W-H (mm)	ORDER CODE
Casambi	150-11-23	030-2531030

DALI-2 SELV device required



Private Residence
Visualisation




Quickinfo


2700 K, 3000 K, 4000 K
 CRI ≥ 90
 up to 105lm/W
 DALI-2

Types



spot line



opal



indirect

**Colour****Light distributions**

spot line

opal


indirect



DESIGN
AWARD
2023

SPOT LINE / OPAL

linear inset 10



flush
mounted

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2


MATERIAL COLOUR

● jet black RAL 9005

LIGHT OPTIC


- spot line
- opal high performance
- indirect

LIGHT INSET 10




SPOT LINE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
6.6 W	2700 K	575lm	300	030-6110::38M
	3000 K	601lm		
	4000 K	601lm		



OPAL HIGH PERFORMANCE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.9 W	2700 K	389lm	500	030-6120::38H
	3000 K	421lm		
	4000 K	421lm		




INDIRECT incl. feeder

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
15.8 W	2700 K	1080lm	1000	030-6330::38M
	3000 K	1140lm		
	4000 K	1190lm		
32 W	2700 K	2170lm	2000	030-6370::38M
	3000 K	2280lm		
	4000 K	2390lm		


MOUNTING ACCESSORY

TYPE	ORDER CODE
3-in-1 mounting tool	030-2611000

for custom cut tracks, Indirect light inset and Pass Through connector



INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour black




Quickinfo


2700 K, 3000 K, 4000 K
 CRI ≥ 90
 up to 91lm/W
 DALI-2

Types

adjustable rod



suspended



Colours



Light distributions

TILA 16



med. flood


TILA 22/32




spot med. flood



glare control via
honeycomb louver



365° rotatable
135° tiltable



free positioning by
cable and hook



flush adapter
mounting



TILA
decorative inset 10

Order options

HOUSING HEIGHT TILA 16	L
80 mm	0
600 mm	1

HOUSING HEIGHT TILA 22	L
100 mm	3
300 mm	4

COLOUR TEMPERATURE	::
2700 K	4
3000 K	5
4000 K	6

CONTROL	
DALI-2	


MATERIAL COLOUR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

MATERIAL COLOUR ACCESSORIES	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE TILA 16	▲
medium 23°	M
flood 31°	F


BEAM ANGLE TILA 22/32	▲
spot 15/17°	S
medium 26/24°	M
flood 43/34°	F

TILA 16



ADJUSTABLE


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
3.3 W	2700 K	177 lm	030-6500::3▲
	3000 K	177 lm	
	4000 K	190 lm	



SUSPENDED


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
3.3 W	2700 K	177 lm	030-66L0::3▲
	3000 K	177 lm	
	4000 K	190 lm	

TILA 22



ADJUSTABLE



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
5.7 W	2700 K	347 lm	030-6530::3▲
	3000 K	354 lm	
	4000 K	385 lm	



SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
5.7 W	2700 K	347 lm	030-66L0::3▲
	3000 K	354 lm	
	4000 K	385 lm	

TILA 32



ADJUSTABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9.7 W	2700 K	788 lm	030-6560::3▲
	3000 K	837 lm	
	4000 K	887 lm	

Mounting accessories



HOOK ceiling mounted


TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	030-100001■

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
TILA 22	20-3	007-1965118
TILA 32	30-3	007-1965168

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white, medium




Quickinfo


2700 K, 3000 K, 4000 K
 CRI ≥ 90
 up to 96lm/W
 DALI-2

Types

square track



round track



Colours



Light distributions

TARO 32



TARO 45



TARO
 decorative inset 10



wallwasher floor
 360° rotatable



wallwasher
 floor

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2	
--------	--

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9



BEAM ANGLE TARO 32

spot 17°	S
medium 24°	M
flood 34°	F

BEAM ANGLE TARO 45


medium 24°	M
flood 36°	F

TARO 32



DOWNLIGHT SQUARE TRACK



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9.6 W	2700 K	764lm	030-6700::3
	3000 K	811lm	
	4000 K	859lm	



DOWNLIGHT ROUND TRACK


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9.6 W	2700 K	764lm	030-6740::3
	3000 K	811lm	
	4000 K	859lm	

TARO 45



DOWNLIGHT SQUARE TRACK



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	949lm	030-6710::3
	3000 K	1010lm	
	4000 K	1060lm	



DOWNLIGHT ROUND TRACK


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	949lm	030-6750::3
	3000 K	1010lm	
	4000 K	1060lm	

TARO 45 wallwasher floor



WALLWASHER FLOOR SQUARE TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	733lm	030-6780::3
	3000 K	791lm	
	4000 K	791lm	



WALLWASHER FLOOR ROUND TRACK


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	733lm	030-6790::3
	3000 K	791lm	
	4000 K	791lm	

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
TARO 32	30-4	007-1965168
TARO 45	42-3	007-1965188


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white, medium



Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90
 up to 77 lm/W
 DALI-2

Type



Colours



Light distributions



med. floor wall
 floor



DESIGN
 AWARD
 2023

GIRA

decorative inset 10



360°
 rotatable



wallwasher
 floor

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2



MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	8




BEAM ANGLE

medium 23°	M
flood 34°	F



GIRA






DOWNLIGHT ROTATABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
18.2 W	2700 K	1160 lm	0 3 0 - 6 4 1 0 :: 3   
	3000 K	1160 lm	
	4000 K	1240 lm	

GIRA wallwasher floor



WALLWASHER FLOOR ROTATABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
19.1 W	2700 K	1260 lm	0 3 0 - 6 4 3 0 :: 3    W
	3000 K	1370 lm	
	4000 K	1480 lm	


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, medium



Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90
 up to 129lm/W
 DALI-2

Types




Colours



Light distribution



365° rotatable
 90° tiltable



free positioning by
 cable and hook



high quality
 glass lens



NOBA

decorative inset 10

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2	
--------	--

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9


MATERIAL COLOUR ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE


wide flood 67°	
----------------	--

NOBA 40



SPOTLIGHT ADJUSTABLE



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
3.5 W	2700 K	403 lm	030-6800
	3000 K	428 lm	
	4000 K	452 lm	



DOWNLIGHT SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
3.5 W	2700 K	403 lm	030-6900
	3000 K	428 lm	
	4000 K	452 lm	


NOBA 50



DOWNLIGHT SUSPENDED


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.2 W	2700 K	747 lm	030-6910
	3000 K	793 lm	
	4000 K	838 lm	

NOBA 60



SPOTLIGHT ADJUSTABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
8.1 W	2700 K	851 lm	030-6820
	3000 K	903 lm	
	4000 K	955 lm	



DOWNLIGHT SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
8.1 W	2700 K	851 lm	030-6920
	3000 K	903 lm	
	4000 K	955 lm	

Mounting accessories



HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	030-100001

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white