

MINO 60 mid lumen

suspended

046-42L4017H



Proyecto / Tipo
Notas
Cantidad / Fecha



RG0 IEC 62471	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Suspendido
blanco , RAL9010 ¹
1210 lm/m
IP20
1420 lm

LED

3000 K
IRC ≥ 90
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.61
MDER 0.55

Óptico

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Eléctrico

non atenuable
sistema 13.3 W
CP1 220-240V
sistema 107 lm/W ³
11 W/m

Físico

cable 1500 mm
longitud 1180 mm
ancho 60 mm
altura 80 mm
3.3 kg

Distribución luminosa



Diseño del producto



¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)

Instrucciones de montaje



Calculadora de iluminación

