

MINO 60 mid lumen

suspended

046-42L3117H



Proyecto / Tipo
Notas
Cantidad / Fecha



RG0 IEC 62471	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Suspendido
blanco , RAL9010 ¹
1320 lm/m
IP20
1150 lm

LED

4000 K
IRC ≥ 90
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _f : 92 , R ₍₁₋₅₎ : 90
MR 0.81
MDER 0.74

Óptico

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Eléctrico

non atenuable
sistema 10.3 W
CP1 220-240V
sistema 112 lm/W ³
12 W/m

Físico

cable 1500 mm
longitud 880 mm
ancho 60 mm
altura 80 mm
2.7 kg

Distribución luminosa



Diseño del producto



¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)

Instrucciones de montaje



Calculadora de iluminación

