

MINO 60 mid lumen

surface

046-41L2118G



Proyecto / Tipo
Notas
Cantidad / Fecha



RG0 IEC 62471	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Superficie
negro , RAL9005 ¹
1160 lm/m
IP20
666 lm

LED

4000 K
IRC ≥ 90
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90
MR 0.81
MDER 0.74

Óptico

Microprismatic
microprismatic
UGR < 19 , ≥ 65° < 3000 cd/m²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Eléctrico

non atenuable
sistema 6.9 W
CP1 220-240V
sistema 97 lm/W ³
12 W/m


Físico

longitud 580 mm
ancho 60 mm
altura 80 mm
1.9 kg

Distribución luminosa



Diseño del producto



¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)

Instrucciones de montaje



Calculadora de iluminación

