

MOVE IN 32 round

trimless

063-8111414F 063-8811117 002-90743



Proyecto / Tipo
Notas
Cantidad / Fecha



General

Techo , Semi-empotrado
cromo
IP20
750 lm

LED

2700 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Óptico

flood
ángulo de haz 34°
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
220-240 V
sistema 11.6 W
inserto 8.7 W
36 Vf
250 mA
CP2
sistema 65 lm/W ²
inserto 86 lm/W ²
1 DALI Addr.

Físico

sin borde
diámetro 63 mm
altura 92 mm
0.28 kg

Orificio

diámetro 54 mm
espesor mín. del techo 9 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

¹ Valor del producto continente a plena carga (no atenuado)
² incl. optical losses and the efficiency of the operating device (converter)

Distribución luminosa



flood 34°

h (m)	E0° (lx)	ø (m)
1	2450	0.61
2	610	1.21
3	270	1.82
4	150	2.42
5	100	3.03

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

