



## MITA circle

suspended

**EN** Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct/indirect light distribution; energy-efficient LEDs with very good colour rendering


**ES** Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; superficie con recubrimiento de pintura en polvo; suspendido; con suspensión ajustable de tubo pendular (cromo), línea de alimentación en tubo pendular; driver instalado en el baldaquino; opcional: cubierta opaca de fijación a recorte de techo con imán disponible como accesorio adicional; reflector de alto brillo con óptica facetada; difusor opal de alta calidad que proporciona una iluminación uniforme; opcionalmente con característica de emisión directa o directa/indirecta; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  80, CRI  $\geq$  90, 3 SDCM  
 UGR  $\leq$  19 / 65°  $\leq$  1500 cd/m<sup>2</sup>  
 up to 160 lm/W  
 L90 @ 50000h  
 DALI-2  
 reflector (UGR  $\leq$  19), opal

### Types


suspended



### Colours



### Light distributions



up to 160 lm/W  
 (high efficiency)



dark chrome  
reflector option



version with  
opal cover



magnetic  
blind cover



DIN EN 12464-1  
UGR  $\leq$  19

## Order options

### SUSPENSION

rod 1000 mm

### COLOUR TEMPERATURE

3000 K (CRI <sub>≥</sub> 90)	0
4000 K (CRI <sub>≥</sub> 90)	1
3000 K (CRI <sub>≥</sub> 80)	5
4000 K (CRI <sub>≥</sub> 80)	6

### CONTROL

DALI-2

### MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

### REFLECTOR COLOUR

✓ chrome	R
● dark chrome	B

### LIGHT OPTIC COVER

reflector (UGR<sub>≤</sub>19)

opal

## Options on request



### SUSPENSION

rod 1000 mm white

rod 1000 mm black

### COLOUR TEMPERATURE

tunable white 2700–6500 K



## MITA circle 450 suspended



UGR  
≤19

cd/m<sup>2</sup>  
≤1500

DALI  
1ADDR.

220-240V

X-PERT

X-PERT

### REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	074-76111 3 ■ ■
	4000 K	4790 lm	
40 W	3000 K	5470 lm	074-76211 3 ■ ■
	4000 K	6230 lm	

### OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
24.9 W	3000 K	2760 lm	074-76111 3 ■ ○
	4000 K	3140 lm	



UGR  
≤19

cd/m<sup>2</sup>  
≤1500

DALI  
1ADDR.

220-240V

X-PERT

X-PERT

### REFLECTOR DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 4170 / ± 3850 lm	074-76511 3 ■ ■
	4000 K	↓ 4750 / ± 4380 lm	

### OPAL DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 3350 / ± 3850 lm	074-76511 3 ■ ○
	4000 K	↓ 3810 / ± 4380 lm	

## Accessories

### BLIND COVER

TYPE	ORDER CODE
MITA circle 450 suspended	074-891162 ■