

# TILA 32 adjustable

MOVE IT 10  
030-6560535M



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



## General

Techo / Pared , Rail \_\_\_\_\_

inclinación máx. 135° \_\_\_\_\_

giro 365° \_\_\_\_\_

gun metal \_\_\_\_\_

IP20 \_\_\_\_\_

837 lm \_\_\_\_\_

inserto óptico 96 lm/W<sup>1</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

IRC ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.53 \_\_\_\_\_

## Óptico

medium \_\_\_\_\_

ángulo de haz 24° \_\_\_\_\_

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Eléctrico

DALI-2 \_\_\_\_\_

48 V \_\_\_\_\_

fijación 9.7 W \_\_\_\_\_

inserto óptico 8.8 W \_\_\_\_\_

CP3 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_


## Físico

diámetro 32 mm \_\_\_\_\_

altura 120 mm \_\_\_\_\_

<sup>1</sup> incluida la consideración de las pérdidas ópticas.  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)


## Distribución luminosa



medium 24°

h (m)	EO° (lx)	ø (m)
1	4450	0.42
2	1110	0.83
3	490	1.25
4	280	1.67
5	180	2.09

## Diseño del producto



## Instrucciones de montaje

