

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-502553GZ



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Suspendido
gris , RAL 9006 <sup>1</sup>
IP20
indirecto 2110 lm
direct 3000 lm
total 5110 lm
3500 lm/m

## LED

3000 K
IRC $\geq 80$
L90 / 50000 h
MacAdam inicial $\leq 3$ SDCM
MR 0.56
MDER 0.51

## Óptico

Microprismatic
microprismatic
UGR $\leq 19$
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

## Eléctrico


DALI-2
220-240 V
sistema 43 W
sistema 119 lm/W <sup>3</sup>
CP1
1 DALI Addr.
29 W/m

## Físico

longitud 1464 mm
ancho 60 mm
altura 80 mm
3.8 kg

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>3</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

