

# MINO 60 high lumen

ceiling / suspended system

007-93M9037 006-16302H 046-4009017



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Suspendido
blanco , RAL9010 <sup>1</sup>
IP20
6140 lm
2050 lm/m

## LED

3000 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.61
MDER 0.55

## Óptico

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


## Eléctrico

DALI-2
220-240 V
sistema 58 W
CP1
sistema 106 lm/W <sup>3</sup>
1 DALI Addr.
19 W/m

## Físico

borde
longitud 3000 mm
ancho 60 mm
altura 80 mm
6.9 kg

## Distribución luminosa



## Diseño del producto



<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Instrucciones de montaje



## Calculadora de iluminación

