

# MINO 60 high lumen

ceiling / suspended system

007-93M4137 006-16122H 046-400401G



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



## General

Techo , Suspendido	
gris , RAL9006 <sup>1</sup>	
IP20	
2570 lm	
2200 lm/m	

## LED

4000 K	
IRC ≥ 90	
L90 / 50000 h	
MacAdam inicial ≤ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>r</sub> : 92 , R <sub>t(1-15)</sub> : 90	
MR 0.81	
MDER 0.74	

## Óptico

High Performance Opal	
opal (lambertsch)	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	


## Eléctrico

DALI-2	
220-240 V	
sistema 23.3 W	
CP1	
sistema 110 lm/W <sup>3</sup>	
1 DALI Addr.	
20 W/m	

## Físico

borde	
longitud 1172 mm	
ancho 60 mm	
altura 80 mm	
2.87 kg	

## Distribución luminosa



## Diseño del producto



<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Instrucciones de montaje



## Calculadora de iluminación

