

MINO 60 high lumen

ceiling / suspended system

007-93M3037 006-16092H 046-4003018



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



General

| |
|------------------------------|
| Techo , Suspendido |
| negro , RAL9005 ¹ |
| IP20 |
| 1790 lm |
| 2050 lm/m |

LED

| |
|---|
| 3000 K |
| IRC ≥ 90 |
| L90 / 50000 h |
| MacAdam inicial ≤ 3 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.61 |
| MDER 0.55 |

Óptico

| |
|--------------------------|
| High Performance Opal |
| opal (lambertsch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


Eléctrico

| |
|-------------------------------|
| DALI-2 |
| 220-240 V |
| sistema 17.5 W |
| CP1 |
| sistema 102 lm/W ³ |
| 1 DALI Addr. |
| 20 W/m |

Físico

| |
|-----------------|
| borde |
| longitud 872 mm |
| ancho 60 mm |
| altura 80 mm |
| 2.14 kg |

Distribución luminosa



Diseño del producto



¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)

Instrucciones de montaje



Calculadora de iluminación

