



STADIO 10

semi-recessed


^{EN} Cylindrical surface mounted miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

^{DE} Zylindrischer Miniatur-Anbaustrahler aus Aluminium; Oberfläche lackiert; Strahlerkopf dreh- und schwenkbar; hochwertige Linsensystem; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; energieeffiziente LEDs mit sehr guter Farbwiedergabe; durchkontaktiertes elektrisches Stecksystem für werkzeuglose Montage; Konverter steckerfertig vorkonfektioniert; Konverter ist separat zu bestellen

Quickinfo

3000 K, 4000 K
 CRI \geq 95 (R9 \geq 90)
 L85 @ 50 000 h
 up to 65 lm per spot
 non DIM, DALI-2

Type



Colours



Light distributions



spot med. flood



CRI \geq 95
 R9 \geq 90



360° rotatable
 90° tiltable




plug & play

Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

MATERIAL COLOUR	
● white aluminium RAL 9006	6
● black RAL 9021	8

BEAM ANGLE	
spot 18°	S
medium 30°	M
flood 39°	F



STADIO 10 semi-recessed



INS. POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
0.6 W	3000K	60lm	0 1 1 - 8 0 0 0 :: 1 ▽ ▲
	4000K	65lm	

light inset incl. connection cable with socket 0.5 m

Electrical accessories

POWER SUPPLY EU 220-240 V AC, 220 mA, 50-60 Hz, □ PC II
incl. power cable 2m + connection cable with plug 1m

TYPE	L·W·H (mm)	ORDER CODE
15W non DIM	115·19·34	0 1 1 - 9 2 1 1 2 1 0
10W DALI-2	145·33·21	0 1 1 - 9 2 1 1 1 3 0

POWER SUPPLY UL 100-120 V AC, 220 mA, 50-60 Hz, □ PC II
incl. connection cable with plug 1m

TYPE	L·W·H (mm)	ORDER CODE
15W non DIM	115·19·34	0 1 1 - 9 2 8 1 2 1 0
25W DALI-2/1-10V	111·22·52	0 1 1 - 9 2 8 1 3 2 0

SPLITTER SERIAL, AWG20


TYPE	L·W·H (mm)	ORDER CODE
splitter 3 × socket / 1 × plug	38·30·10	0 1 1 - 9 2 2 8 3 0 0
splitter 6 × socket / 1 × plug	55·32·10	0 1 1 - 9 2 2 8 6 0 0

Other accessories


EXTENSION CABLE

TYPE	L (mm)	ORDER CODE
1 × socket / 1 × plug	1000	0 1 1 - 9 2 2 1 1 2 0
1 × socket / 1 × plug	2000	0 1 1 - 9 2 2 1 1 4 0
1 × socket / 1 × plug	4000	0 1 1 - 9 2 2 1 1 8 0


Light distributions



spot 18°



medium 30°



flood 39°

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 95, medium lens, colour black