



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



General

Vitrina , De pie \_\_\_\_\_

rotación 360° \_\_\_\_\_

aluminio blanco , RAL9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

249 lm \_\_\_\_\_

LED

4000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 94 , R<sub>f(1-5)</sub>: 96 \_\_\_\_\_

MR 0.87 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

Óptico

spot \_\_\_\_\_

ángulo de haz 18° \_\_\_\_\_

Eléctrico

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

4.6 W \_\_\_\_\_

CP3 24V \_\_\_\_\_

54 lm/W \_\_\_\_\_

Físico


longitud 400 mm \_\_\_\_\_

ancho 11 mm \_\_\_\_\_

altura 29 mm \_\_\_\_\_

<sup>1</sup> Código RAL

Distribución luminosa



spot 18°

h (m)	EO° (lx)	ø (m)
1	1820	0.32
2	450	0.64
3	200	0.96
4	110	1.28
5	70	1.59

Diseño del producto

