



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Vitrina , Empotrado \_\_\_\_\_

inclinable máx 90° \_\_\_\_\_

rotación 360° \_\_\_\_\_

negro , RAL9021 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

358 lm \_\_\_\_\_

**LED**

4000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 94 , R<sub>(1-15)</sub>: 96 \_\_\_\_\_

MR 0.87 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

**Óptico**

medium \_\_\_\_\_

ángulo de haz 30° \_\_\_\_\_

**Eléctrico**

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

5.0 W \_\_\_\_\_

CP3 24V \_\_\_\_\_

72 lm/W \_\_\_\_\_

24 V \_\_\_\_\_

**Físico**


longitud 400 mm \_\_\_\_\_

ancho 11 mm \_\_\_\_\_

altura 29 mm \_\_\_\_\_

<sup>1</sup> Código RAL


Distribución luminosa



medium 30°

h (m)	E0° (lx)	ø (m)
1	1090	0.54
2	270	1.07
3	120	1.61
4	70	2.15
5	40	2.68

Diseño del producto



Instrucciones de montaje

