



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Vitrina , Empotrado \_\_\_\_\_

inclinable máx 90° \_\_\_\_\_

rotación 360° \_\_\_\_\_

negro , RAL9021 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

244 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 102 , R<sub>r</sub>: 94 , R<sub>(1-15)</sub>: 95 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

**Óptico**

spot \_\_\_\_\_

ángulo de haz 18° \_\_\_\_\_

**Eléctrico**

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

4.9 W \_\_\_\_\_

CP3 24V \_\_\_\_\_

50 lm/W \_\_\_\_\_

24 V \_\_\_\_\_

**Físico**


longitud 400 mm \_\_\_\_\_

ancho 11 mm \_\_\_\_\_

altura 29 mm \_\_\_\_\_

<sup>1</sup> Código RAL


Distribución luminosa



spot 18°

h (m)	E0° (lx)	ø (m)
1	1780	0.32
2	450	0.64
3	200	0.96
4	110	1.28
5	70	1.59

Diseño del producto



Instrucciones de montaje

