

MITA circle 450 opal

direct / indirect soft

ceiling

074-75311370



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



RG0 IEC 62471	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Superficie	
blanco , RAL9016 ¹	
IP20	
indirecto 127 lm	
direct 2510 lm	
total 2640 lm	

LED

4000 K	
IRC ≥ 90	
L90 / 50000 h	
seguridad fotobio. RG 0 - sin riesgo	
MacAdam inicial ≤ 3 SDCM	
R _g : 99 , R _r : 92 , R ₍₁₋₁₅₎ : 90	
MR 0.81	
MDER 0.74	

Óptico

Opal	
symmetric	
P _{stLM} ≤ 1.0 ²	
SVM ≤ 0.4 ²	


Eléctrico

DALI-2	
sistema 24.9 W	
CP1 220-240V	
sistema 106 lm/W ³	
1 DALI Addr.	


Físico

diámetro 426 mm	
altura 72 mm	

Distribución luminosa



Diseño del producto



¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)
³ incl. optical losses and the efficiency of the operating device (converter)

Instrucciones de montaje



Calculadora de iluminación

