

# MICROPRISMATIC UGR < 19

MOVE IT PRO

086-6240130 086-6040000P



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



## General

Techo , Rail	
IP20	
1790 lm	
715 lm/m	

## LED

4000 K	
IRC ≥ 90	
L90 / 50000 h	
MacAdam inicial ≤ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 92 , R <sub>(1-5)</sub> : 90	
MR 0.81	
MDER 0.74	

## Óptico

Microprismatic	
microprismatic	
UGR < 19 , ≥65° <3000 cd/m <sup>2</sup>	
PstLM ≤ 1.0 <sup>1</sup>	
SVM ≤ 0.4 <sup>1</sup>	

## Eléctrico


DALI-2	
220-240 V	
sistema 17.9 W	
CP2	
sistema 100 lm/W <sup>2</sup>	
1 DALI Addr.	
7 W/m	

## Físico

longitud 2500 mm	
ancho 43 mm	
altura 13 mm	

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

## Distribución luminosa



## Diseño del producto



## Calculadora de iluminación

