

MICROPRISMATIC UGR < 19

MOVE IT PRO

086-6240030 086-6040000P



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



General

| |
|--------------|
| Techo , Rail |
| IP20 |
| 1650 lm |
| 662 lm/m |

LED

| |
|--|
| 3000 K |
| IRC ≥ 90 |
| L90 / 50000 h |
| MacAdam inicial ≤ 3 SDCM |
| R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89 |
| MR 0.61 |
| MDER 0.55 |

Óptico

| |
|-------------------------------|
| Microprismatic |
| microprismatic |
| UGR ≤ 19 , ≥ 65° < 3000 cd/m² |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Eléctrico


| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| sistema 17.9 W |
| sistema 92 lm/W ² |
| CP2 |
| 1 DALI Addr. |
| 7 W/m |

Físico

| |
|------------------|
| longitud 2500 mm |
| ancho 43 mm |
| altura 13 mm |

¹ Valor del producto continente a plena carga (no atenuado)
² incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

Distribución luminosa



Diseño del producto



Calculadora de iluminación

