

# MICROPRISMATIC UGR < 19

MOVE IT PRO

086-6210930 086-6010000P



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



## General

Techo , Rail	
IP20	
662 lm	
662 lm/m	

## LED

2700 K	
IRC ≥ 90	
L90 / 50000 h	
MacAdam inicial ≤ 3 SDCM	
R <sub>g</sub> : 101 , R <sub>f</sub> : 90 , R <sub>f(1-15)</sub> : 88	
MR 0.51	
MDER 0.46	

## Óptico

Microprismatic	
microprismatic	
UGR ≤ 19 , ≥65° <3000 cd/m <sup>2</sup>	
PstLM ≤ 1.0 <sup>1</sup>	
SVM ≤ 0.4 <sup>1</sup>	

## Eléctrico


DALI-2	
220-240 V	
sistema 8.0 W	
sistema 83 lm/W <sup>2</sup>	
CP2	
1 DALI Addr.	
8 W/m	

## Físico

longitud 1000 mm	
ancho 43 mm	
altura 13 mm	

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>2</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Calculadora de iluminación

