

# SASSO 60 square downlight

trim 2 lamps

048-2612214M 048-2699318 002-90742



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	UGR ≤16	cd/m² ≤3000	CRI ≥90	X-PERT
------------------	----------	--------	------------	----------------	------------	--------

## General

Techo , Empotrado
plata mate
Set de montaje negro intenso
parte delantera IP44 , parte trasera IP20
1850 lm

## LED

3500 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 89
MR 0.7
MDER 0.64

## Óptico

medium
beam angle 21°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

non atenuable
20.5 W
inserto 8.7 W
36 Vf
250 mA
total de insertos 17.4 W
CP2 220-240V
90 lm/W
inserto 107 lm/W

## Físico


borde
length 147 mm
width 81 mm
altura 48 mm
0.28 kg

## Orificio

length 138 mm
width 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 90 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

