



SASSO 100 square

recessed


EN Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable cuadrado; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie lacada; posibilidad de instalar distintas carcasas; elección de la característica de radiación; ajustable o fija simétrica o asimétrica; variantes de radiación simétrica: proyección precisa con óptica de lente de alta calidad; variantes con emisión asimétrica: reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; Chip on Board que proporciona una máxima eficiencia (ADJUSTABLE y DOWNLIGHT); no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
CWD 1800–3000 K
CRI ≥ 90, 2 SDCM
up to 125 lm/W
L80 @ 50 000 h
non DIM, DALI-2
↓ IP 44 / ↑ IP 20

Types

trim		75 95 (each)
	□ 118	
trimless		75 95 (each)
	□ 97	
double trim		75 95 (each)
	218x118	

Housing colours



Inset colours



Light distributions



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)



60 mm
recess depth



CWD
1800–3000 K



CRI ≥ 95
2 SDCM

Order options

COLOUR TEMPERATURE ADJ. / DOWNLIGHT / WW

2700K	9
3000K	0
3500K	2
4000K	1
CWD 1800-3000K*	

*only for DALI-2; not for DIN-RAIL LED Driver

COLOUR TEMPERATURE WALLWASHER FLOOR

2700K	4
3000K	5
4000K	6
CWD 1800-3000K*	

*only for DALI-2; not for DIN-RAIL LED Driver

INSET COLOUR

<input type="radio"/> traffic white RAL 9016 (UGR _{≤22})	7
<input type="radio"/> matt silver (UGR _{≤19})	4
<input type="radio"/> jet black RAL 9005 (UGR _{≤16})	1
<input type="radio"/> gold dust RAL 260-M (UGR _{≤19})	9

BEAM ANGLE

spot 19°*	S
medium 34°	M
floor 45°*	F
wide flood 65°	W
super wide flood 70°**	X

*not available for CWD

**only for inset colour white

Options on request

COLOR RENDERING INDEX

CRI ≥ 95, 2 SDCM

CONTROL

Casambi

MOUNTING SET

acoustic soft ceilings

POWER SUPPLY

DIM 1-10V

Light distributions



wallwasher



wallwasher floor

INSET POWER is the current

consumption excluding any ballast

LUMINOUS FLUX value calculated for

3000K, CRI ≥ 90, colour white, wide flood

2700K -5%, 4000K +5%



SASSO 100 square



ADJUSTABLE (↓ IP 40 | ↑ IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
15.2W 36 Vf 450mA	1760lm	0 4 8 - 2 7 3 0 :: 1 □ ▲
22.7W 36 Vf 650mA	2420lm	0 4 8 - 2 7 3 0 :: 1 □ ▲
23.8W 36 Vf 700mA	CWD 2280lm	0 4 8 - 2 7 3 0 E 1 □ ▲

DOWNLIGHT (↓ IP 44 | ↑ IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
15.8W 36 Vf 450mA	↓IP44 1770lm	0 4 8 - 2 7 1 0 :: 1 □ ▲
23.6W 36 Vf 650mA	↓IP44 2430lm	0 4 8 - 2 7 1 0 :: 1 □ ▲
23.8W 36 Vf 700mA	↓IP40 CWD 2290lm	0 4 8 - 2 7 1 0 E 1 □ ▲



WALLWASHER (IP20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
15.8W 36 Vf 450mA	1750lm	0 4 8 - 2 7 5 0 :: 1 □ A
23.6W 36 Vf 650mA	2700lm	0 4 8 - 2 7 5 0 :: 1 □ A

WALLWASHER / FLOOR (IP20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
16.3W 36 Vf 500mA	1700lm	0 4 8 - 2 7 5 0 :: 1 □ W
23.4W 36 Vf 700mA	2310lm	0 4 8 - 2 7 5 0 :: 1 □ W

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 2 7 9 7 1 1 7

MOUNTING SET WITH TRIM for intermediate ceilings 2-25mm

TYPE	ORDER CODE
1 lamp	0 4 8 - 2 7 9 7 3 1 ■
2 lamps	0 4 8 - 2 7 9 9 3 1 ■

CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (mm)	ORDER CODE
primed concrete ceilings*	614-307-120	0 4 8 - 2 6 9 5 1 1 0

*order mounting set separately, not applicable for 2 lamps mounting set with trim

Electrical accessories

POWER SUPPLY 220-240V AC, 50-60 Hz, □ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450mA non DIM	η 88 %	143-43-30	0 0 2 - 9 0 7 6 6
450mA DALI-2	η 88 %	143-43-30	0 0 2 - 9 0 7 6 7
650mA non DIM	η 88 %	143-43-30	0 0 2 - 9 0 7 8 0
650mA DALI-2	η 88 %	143-43-30	0 0 2 - 9 0 7 8 9
700mA non DIM	η 80 %	143-43-30	0 0 2 - 9 0 7 7 4
700mA DALI-2	η 88 %	143-43-30	0 0 2 - 9 0 7 7 6

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4-12mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4-12mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160W 48V DC constant voltage		
LED DRIVER DALI-2 DT6 1-2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200-1050mA settable const. current		
2x 42W 48V DC U _{OUT} 10-40V		

for more details and components see page 981