

SASSO 100 round downlight

trim

048-2700014S 048-2796318 002-90766



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
IP20 IP44
X-PERT
X-PERT

General

Techo , Empotrado
plata mate
Set de montaje negro intenso
parte delantera IP44 , parte trasera IP20
1490 lm

LED

3000 K
IRC ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _r : 90 , R _{t(1-15)} : 87
MR 0.6
MDER 0.54

Óptico

spot
ángulo de haz 19°
UGR < 13 , $\geq 65^\circ$ <3000 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
sistema 17.9 W
inserto 15.2 W
36 V _f
450 mA
CP2 220-240V
sistema 83 lm/W ²
inserto 98 lm/W ³

Físico


borde
diámetro 118 mm
altura 75 mm
0.47 kg

Orificio


diámetro 108 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Valor del producto continente a plena carga (no atenuado)
² incl. optical losses and the efficiency of the operating device (converter)
³ incl. optical losses

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

