



## SASSO 60/100 round

semi-recessed

**EN** Cylindrical semi-recessed spotlight made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; choice of adj. sym. or asym. radiation characteristic; variants with sym. radiation characteristic: precise due to high quality lens system; variants with asym. radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE); no multiple shadows; efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable

**ES** Foco cilíndrico de aluminio para el montaje semiempotrado en 2 tamaños; inserto lumin. pintado; carcasa con recubr. de polvo; cuerpo luminoso insertable en la placa de montaje por enclavamiento y sin necesidad de herramienta; proyección sim. o asim. regulable; variantes de radiación sim.: precisa con óptica lente alta calidad; variantes de radiación asim.: reflector de alta calidad con superficie microfacetada metaliz. con aluminio; Chip on Board que proporciona una máxima eficiencia (ADJUSTABLE); no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática; convertidor externo para inserción en el techo, adecuado para cableado pasante

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI ≥ 90, 2 SDCM  
 SASSO 60 up to 116 lm/W  
 SASSO 100 up to 120 lm/W  
 L80 @ 50 000 h  
 non DIM, DALI-2

### Types



### Housing colours



### Inset colours



### Light distributions

SASSO 60



SASSO 100



wallwasher and  
ww floor inset



glare control  
(UGR ≤ 16)



easy mounting;  
no visible screws



CWD  
1800–3000 K



CRI ≥ 95  
2 SDCM

## Order options

### COLOUR TEMPERATURE ADJUSTABLE

|        |   |
|--------|---|
| 2700K  | 9 |
| 3000K  | 0 |
| 3500K* | 2 |
| 4000K  | 1 |

\*only for SASSO 60

### COLOUR TEMPERATURE WALLWASHER & WW FLOOR

|       |   |
|-------|---|
| 2700K | 4 |
| 3000K | 5 |
| 4000K | 6 |

### HOUSING COLOUR

|   |   |
|---|---|
| <input type="radio"/> traffic white RAL 9016        | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 1 |

### INSET COLOUR

|   |   |
|---|---|
| <input type="radio"/> traffic white RAL 9016 (UGR $\leq$ 22)        | 7 |
| <input type="radio"/> matt silver (UGR $\leq$ 19)                   | 4 |
| <input checked="" type="radio"/> jet black RAL 9005 (UGR $\leq$ 16) | 1 |
| <input type="radio"/> gold dust RAL 260-M (UGR $\leq$ 19)           | 9 |

### BEAM ANGLE

|                 |   |
|-----------------|---|
| <b>SASSO 60</b> | ▲ |
| spot 11°        | S |
| medium 21°      | M |
| flood 42°       | F |
| wide flood 54°  | W |

### BEAM ANGLE

|                  |   |
|------------------|---|
| <b>SASSO 100</b> | ▲ |
| spot 19°         | S |
| medium 34°       | M |
| flood 45°        | F |
| wide flood 65°   | W |

## Options on request

### COLOUR RENDERING INDEX

CRI  $\geq$  95, 2 SDCM

### COLOUR TEMPERATURE

CWD 1800–3000K

not for WW & WWF version

### CONTROL

Casambi



## SASSO 60 round semi-recessed



### ADJUSTABLE

|                    |                      |                   |
|--------------------|----------------------|-------------------|
| <b>INSET POWER</b> | <b>LUMINOUS FLUX</b> | <b>ORDER CODE</b> |
| 8.7W 36 Vf 250 mA  | 873lm                | 048-3101::1■▲▲    |



### WALLWASHER

|                    |                      |                   |
|--------------------|----------------------|-------------------|
| <b>INSET POWER</b> | <b>LUMINOUS FLUX</b> | <b>ORDER CODE</b> |
| 8.2W 27 Vf 300 mA  | 635lm                | 048-3701::1■▲A    |

### WALLWASHER / FLOOR

|                    |                      |                   |
|--------------------|----------------------|-------------------|
| <b>INSET POWER</b> | <b>LUMINOUS FLUX</b> | <b>ORDER CODE</b> |
| 8.2W 27 Vf 300 mA  | 633lm                | 048-3701::1■▲W    |

## SASSO 100 round semi-recessed



### ADJUSTABLE

|                    |                      |                   |
|--------------------|----------------------|-------------------|
| <b>INSET POWER</b> | <b>LUMINOUS FLUX</b> | <b>ORDER CODE</b> |
| 15.2W 36 Vf 450 mA | 1830lm*              | 048-3401::1■▲▲    |

\*reflector white flood

## Electrical accessories

### POWER SUPPLY 220-240V AC, 50-60Hz, □ PC II

| TYPE             | EFFICIENCY  | L-W-H (mm) | ORDER CODE |
|------------------|-------------|------------|------------|
| 250 mA   non DIM | $\eta$ 85 % | 65-39-20   | 002-90742  |
| 250 mA   DALI-2  | $\eta$ 85 % | 143-43-30  | 002-90746  |
| 300 mA   non DIM | $\eta$ 85 % | 85-40-22   | 002-90771  |
| 300 mA   DALI-2  | $\eta$ 88 % | 143-43-30  | 002-90762  |
| 450 mA   non DIM | $\eta$ 88 % | 143-43-30  | 002-90766  |
| 450 mA   DALI-2  | $\eta$ 88 % | 143-43-30  | 002-90767  |

### THROUGH WIRING CONNECTION BOX for SASSO 100

| TYPE                         | L-W-H (mm) | ORDER CODE  |
|------------------------------|------------|-------------|
| non DIM cable $\phi$ 4–12 mm | 105-58-30  | 005-2531110 |
| DALI cable $\phi$ 4–12 mm    | 105-58-30  | 005-2551110 |

### DIN RAIL COMPONENTS

| TYPE                                       | W-H-D (mm) | ORDER CODE  |
|--|------------|-------------|
| POWER SUPPLY 220-240V AC                   | 72-90-63   | 005-6520210 |
| 160W   48V DC constant voltage             |            |             |
| LED DRIVER DALI-2 DT6 1–2 addr.            | 36-88-59   | 005-6121030 |
| 200–1050 mA settable const. current        |            |             |
| 2 × 42W   48V DC   U <sub>OUT</sub> 10–40V |            |             |

for more details and components see page 981

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for 3000K, CRI  $\geq$  90, colour white, flood 2700K -4%, 4000K +6%