


## Quickinfo

4000K  
 CRI ≥ 90, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 3000 cd/m²  
 up to 117 lm/W  
 L95 @ 50 000 h  
 DALI-2  
 microprismatic (UGR ≤ 19)

## Types



## Colours



## Light distribution



## TASK circle

suspended

**EN** Ring-shaped suspended luminaire, consisting of single elements in quarter circle or rectangular shape; Luminaire housing made of aluminium – rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; incl. feed; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-eff. LEDs – very good colour rendering; canopy for through wiring


**FR** Luminaire suspendu circulaire, composé d'éléments individuels en forme de quart-de-cercle ou de rectangle ; Corps du luminaire en aluminium - bords arrondis ; forme extrême plate (15mm seulement) ; surface thermolaquée ; suspension à câble réglable en hauteur sans outil ; système de montage rapide, convivial et sans outil ; incl. conduit d'alimentation ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; partie indirecte avec platines dédiées pour un flux lumineux accru et un éclairage maximal du plafond ; éclairage parfaitement homogène ; LED à haut rend. énerg. – excellent rendu coul. ; cache-piton pour câblage continu




Diia® standards  
251, 252, 253



click-system



DIN EN 12464-1  
UGR ≤ 19



CRI ≥ 98  
XPECTRUM

Order options

COLOUR TEMPERATURE

4000 K

CONTROL

DALI-2

LUMINAIRE COLOUR

- ☐ pure white RAL 9010
- ☒ jet black RAL 9005

LIGHT OPTIC COVER

microprismatic (UGR ≤ 19)

Options on request



COLOUR RENDERING INDEX

CRI ≥ 80

CRI ≥ 98 XPECTRUM

FORM

for other configurations see  
TASK S suspended system



TASK circle suspended



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
169 W	4000 K	↓ 12900 / ↑ 6870 lm	0 5 9 - 5 2 8 1 1 3 <input checked="" type="checkbox"/> K


TASK long circle suspended



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
252 W	4000 K	↓ 20200 / ↑ 10460 lm	0 5 9 - 5 2 8 2 1 3 <input checked="" type="checkbox"/> K

Technical data




**TASK long circle**  
252 W, 4000 K, direct/indirect power

ROOM VALUES	
Room dimensions	5,4 × 4 × 2,8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE .....	
Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E <sub>m</sub> )	> 500 lx
Uniformity (U <sub>0</sub> )	> 0.6

GLARE EVALUATION	
Table Classification X=4H   Y=8H   S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Light distribution



microprismatic  
direct/indirect power

**LUMINOUS FLUX** value calculated for  
CRI ≥ 90, colour white, cover microprismatic