

## TASK square

free standing


**EN** Free standing luminaire with square luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); steel round downpipe; pedestal with recess for table base; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3 m) with safety plug

**FR** Lampadaire à tête de luminaire carrée en aluminium et bords arrondis ; forme extrêm. plate (15 mm seulement) ; Tube acier rond ; pied avec échancrure pour pied de table ; surface thermolaquée ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; partie indirecte avec platines dédiées pour un flux lumineux accru et un éclairage maximal du plafond ; éclairage parfaitement homogène ; LED économes en énergie à restitution de couleur élevée ; interrupteur intégré dans le tube ; incl. câble raccordement (3m) avec fiche contact de protection

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90, 3 SDCM  
 UGR  $\leq$  19 / 65°  $\leq$  3000 cd/m<sup>2</sup>  
 up to 143 lm/W  
 L90 @ 50 000h  
 touch DIM on pole  
 brightness & presence sensor  
 microprismatic (UGR  $\leq$  19)

### Type




### Colours



### Light distribution




direct  
indirect



suitable for  
fourfold workstation



control by touch  
DIM on pole



CRI  $\geq$  98  
XPECTRUM

## Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

CONTROL	
touch DIM on pole	5
ESSENTIAL sensor (brightness & presence)	7


MATERIAL COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	6
● jet black RAL 9005	8
● special colours  p.992	X

LIGHT OPTIC COVER
microprismatic (UGR ≤ 19)


## Options on request

COLOUR RENDERING INDEX
CRI ≥ 80
CRI ≥ 98 XPECTRUM


CONTROL
dynamic daylight control




## TASK square free standing



### DIRECT / INDIRECT POWER


SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
92W	3000K	↓ 2280 / ± 10000lm	0 5 9 - 2 9 3 2  Z
	4000K	↓ 2420 / ± 10700lm	

## Light distribution



microprismatic  
direct/indirect power

## Technical data



**TASK square free standing**  
92W, 4000K, direct/indirect power

### ROOM VALUES

Room dimensions	7.2 × 4 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8

### CALCULATION SURFACE .....

Surface dimensions	4.8 × 0.6 m
Surface height	0.75 m
Average illuminance (E <sub>m</sub> )	> 500 lx

### GLARE EVALUATION

Table Classification X=4H   Y=8H   S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
65° ≤ 3000 cd/m <sup>2</sup>	