

# MOVE IN 45 round

trimless

063-8121518M 063-8812117 002-90724



Projet / Type

Notes

Quantité / Date



220-240V

X-PERT

UGR ≤ 10

CRI ≥ 90

X-PERT

## Général

Plafond , Demi-encastré

noir , RAL9005 <sup>1</sup>

IP20

1270 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

## Optique

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

non DIM

15.9 W

insert 13.5 W

36 Vf

400 mA

CP2 220-240V

80 lm/W

## Physique

sans bord

diameter 75 mm

hauteur 106 mm

0.53 kg

## Découpe


diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

## Répartition de la lumière



medium 24°

h (m)	E0° (lx)	ø (m)
1	6120	0.43
2	1530	0.86
3	680	1.30
4	380	1.73
5	240	2.16

## Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

