

MOVE IN 45 round

trimless

063-8121517M 063-8812117 002-90724



Projet / Type

Notes

Quantité / Date



220-240V

X-PERT

UGR ≤ 10

CRI ≥ 90

X-PERT

Général

Plafond , Demi-encastré

blanc , RAL9016 ¹

IP20

1270 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.59

MDER 0.53

Optique

medium

beam angle 24°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

15.9 W

insert 13.5 W

36 Vf

400 mA

CP2 220-240V

80 lm/W

Physique

sans bord

diameter 75 mm

hauteur 106 mm

0.53 kg

Découpe

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



medium 24°

h (m)	E0° (lx)	ø (m)
1	6120	0.43
2	1530	0.86
3	680	1.30
4	380	1.73
5	240	2.16

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

