

MOVE IN 45 round

trim

063-8121418F 063-8822117 002-90724



Projet / Type _____

Notes _____

Quantité / Date _____



220-240V X-PERT UGR ≤ 10 CRI ≥ 90 X-PERT

Général

Plafond , Demi-encasté
noir , RAL9005 ¹
Set de montage blanc signalisation
IP20
1230 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R_g: 99 , R_r: 91 , R_{t(1-15)}: 89
MR 0.53
MDER 0.48

Optique

flood
beam angle 36°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

non DIM
15.9 W
insert 13.5 W
36 Vf
400 mA
CP2 220-240V
77 lm/W

Physique

bord
diamètre 77 mm
hauteur 107 mm
0.57 kg

Découpe

diamètre 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 200 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)


Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

