

MOVE IN 45 round

trimless

063-8121417F 063-8812117 002-90724



Projet / Type

Notes

Quantité / Date



220-240V

X-PERT

UGR ≤ 10

CRI ≥ 90

X-PERT

Général

Plafond , Demi-encastré

blanc , RAL9016 ¹

IP20

1230 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.53

MDER 0.48

Optique

flood

beam angle 36°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

15.9 W

insert 13.5 W

36 Vf

400 mA

CP2 220-240V

77 lm/W

Physique

sans bord

diameter 75 mm

hauteur 106 mm

0.53 kg

Découpe


diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

