

TASK ACOUSTIC 1200

round

suspended

059-579236W



Projet / Type


Notes

Quantité / Date



Élément acoustique en feutre PET de haute qualité, autoportant, avec des caractéristiques d'absorption acoustique, composé à 50% de PET recyclé ; forme ronde ; esthétique et haptique de la surface de haute qualité, blanc ; déviations de couleurs possibles ; absorption du bruit direct grâce à la façade en non-tissé, ainsi qu'absorption du bruit réfléchi par le plafond/mur grâce à une couche de non-tissé supplémentaire au dos ; pour de meilleures performances acoustiques ; montage suspendu avec suspension de câble de 1500 mm ; réglage de la hauteur sans outil de l'élément acoustique ;

Dessin de fabrication



Général

Plafond , Suspendu

blanc

Physique

panneau seulement

diamètre 1155 mm

hauteur 30 mm

4.2 kg

Acoustics

Alpha w (α_w) up to 0.95 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.95 ¹

SAA up to 0.91 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Notice de montage



TASK

ACOUSTIC 1200

round

suspended

059-579236W



Projet / Type

Notes

Quantité / Date

product-datasheet.soundabsorption

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.6	0.77	1.23	1.53	1.8	1.87

product-datasheet.acoustic-coefficients-diagram

