

TASK

ACOUSTIC 600

square

surface


059-579114X



Projet / Type


Notes

Quantité / Date



Élément acoustique en feutre PET de haute qualité, autoportant, avec des caractéristiques d'absorption acoustique, composé à 50% de PET recyclé ; forme carrée ; esthétique et haptique de la surface de haute qualité, couleurs acoustiques ; déviations de couleurs possibles ; absorption du bruit direct grâce à la façade en non-tissé, ainsi qu'absorption du bruit réfléchi par le plafond/mur grâce à une couche de non-tissé supplémentaire au dos ; pour de meilleures performances acoustiques ; pour montage apparent mur/plafond ;

Dessin de fabrication



Général

Plafond , Surface

couleurs acoustiques

Physique

panneau seulement

longueur 600 mm

largeur 600 mm

hauteur 30 mm

1.9 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.6 <sup>1</sup>

SAC (sound absorption class) up to C <sup>1</sup>

NRC up to 0.75 <sup>1</sup>

SAA up to 0.76 <sup>1</sup>

<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Notice de montage



TASK ACOUSTIC 600

square

surface

059-579114X



Projet / Type

Notes

Quantité / Date

product-datasheet.soundabsorption

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.02	0.11	0.25	0.36	0.36	0.36

product-datasheet.acoustic-coefficients-diagram

