

# LINEA opal / 1 spot

wall system

058-6142517BH



Projet / Type

Notes

Quantité / Date



## Général

Mur , Surface

inclinaison max 89°

blanc , RAL9010 <sup>1</sup>

IP20

172 lm

## LED

3000 K

CRI ≥ 97<sup>2</sup>-90<sup>3</sup>

L95 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

sécurité photobio. RG 0 - aucun risque

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 92<sup>2</sup>-99<sup>3</sup>, R<sub>f</sub>: 86<sup>2</sup>-91<sup>3</sup>, R<sub>(1-15)</sub>: 94<sup>2</sup>-89<sup>3</sup>

MR 0.53<sup>2</sup>-0.61<sup>3</sup>

MDER 0.48<sup>2</sup>-0.55<sup>3</sup>

## Optique

flood

angle de faisceau 30°

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

High Performance Opal

## Electrique

non DIM

2.7<sup>2</sup>-17.6<sup>3</sup> W

CP1 220-240V

64<sup>2</sup>-100<sup>3</sup> lm/W

## Physique

longueur 706 mm

largeur 40 mm


hauteur 100 mm

gauche

<sup>1</sup> Code RAL <sup>2</sup> Projecteur <sup>3</sup> Linéaire

<sup>4</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière




flood 30°

Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

## Dessin de fabrication



## Notice de montage

