



MIRA 150/200

recessed

EN Round or square luminaire housing in die-cast aluminium, available in 2 different sizes; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; lighting level recessed; completely homogeneously illuminated, satinised or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion

FR Corps de luminaire rond ou carré en aluminium moulé, disponible dans 2 tailles ; avec bord continu ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; montage sans outil avec fermeture par ressort à déclic ; niveau de luminaire en retrait ; cache PMMA, à éclairage parfaitement homogène, satiné ou microprismatique ; LED économes en énergie à restitution de couleur élevée ; convertisseur externe pour fente plafond

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 128 lm/W
L80 @ 50 000 h
non DIM, DALI-2
IP20, IP54

Types

MIRA round



MIRA square



Colours




Light distribution



direct



90 mm
recess depth



weatherproof
protection (IP54)

Order options

IP RATING	<input type="radio"/>
IP 20	0
IP 54	8

COLOUR TEMPERATURE	<input type="checkbox"/>
3000K	5
4000K	6

CONTROL	<input type="checkbox"/>
non DIM	1
DALI-2	3

MATERIAL COLOUR	<input checked="" type="checkbox"/>
<input type="radio"/> pure white RAL 9010	7
<input checked="" type="radio"/> jet black RAL 9005	8


LIGHT OPTIC COVER	<input checked="" type="checkbox"/>
opal	O
microprismatic	P

Options on request


EMERGENCY LIGHT	
1h accupack	
3h accupack	

MOUNTING SET	
exposed concrete mounting housing	

COLOUR TEMPERATURE	
2700 K	




MIRA 150 round trim




DOWNLIGHT

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
13 W	3000K	1510lm	<input type="checkbox"/> 5 2 - 9 3 2 3 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	1670lm	
18.6 W	3000K	2030lm	<input type="checkbox"/> 5 2 - 9 3 2 4 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	2240lm	




MIRA 200 round trim




DOWNLIGHT

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
27.9 W	3000K	3050lm	<input type="checkbox"/> 5 2 - 9 4 2 3 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	3360lm	
50 W	3000K	4830lm	<input type="checkbox"/> 5 2 - 9 4 2 4 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	5330lm	




MIRA 150 square trim




DOWNLIGHT

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
13 W	3000K	1510lm	<input type="checkbox"/> 5 2 - 9 3 4 3 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	1670lm	
18.6 W	3000K	2030lm	<input type="checkbox"/> 5 2 - 9 3 4 4 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	2240lm	



MIRA 200 square trim




DOWNLIGHT

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
27.9 W	3000K	3050lm	<input type="checkbox"/> 5 2 - 9 4 4 3 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	3360lm	
50 W	3000K	4830lm	<input type="checkbox"/> 5 2 - 9 4 4 4 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	5330lm	

Accessories

THROUGH WIRING CONNECTION BOX



TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4-12mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø4-12mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

not necessary for 49W versions, converter already has the option for through-wiring