

ARY adjustable rod suspended

MOVE IT 25 / 25 S / 45

050-0631438F



Projet / Type

Notes

Quantité / Date



Général

Plafond , Rail Suspendu

inclinaison max 90°

rotation 265°

noir , RAL 9005 ¹

IP20

1040 lm

insert optique 87 lm/W²

LED

2700 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 96 , R_r: 90 , R_{t(1-15)}: 88

MR 0.55

MDER 0.5

Optique

flood

angle de faisceau 44°

P_{stLM} ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrique

DALI-2

48 V

luminaire 14.1 W

insert optique 12.0 W

CP3

1 DALI Addr.

Physique

barre de 1500 mm avec crochet

diamètre 47 mm


hauteur 110 mm

0.5 kg

¹ Code RAL ² y compris la prise en compte des pertes optiques.

³ Valeur du produit contenant à pleine charge (non atténué)


Répartition de la lumière



flood 44°

h (m)	EO° (lx)	ø (m)
1	1930	0.82
2	480	1.64
3	210	2.45
4	120	3.27
5	80	4.09

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

