



MOVE IT 25 S system

trimless / surface / suspended

EN Thin extruded aluminium profile with 31mm height and 28mm width groove; optionally for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5mm ceiling thickness; or for wall-/ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional with indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking

FR Profil extrudé en aluminium plat avec 31mm de hauteur et 28mm de largeur de joint ; au choix pour un encastrement sans bord dans des plafonds en placoplâtre (montage mural ou au plafond) d'une épaisseur de 12,5mm ; ou pour un montage en surface au mur ou au plafond ou pour un montage suspendu (suspension par câble, réglage de la hauteur sans outil, câble d'alimentation noir inclus) ; en option avec composants lumineux indirects pour une accentuation supplémentaire du plafond ; pour les systèmes d'éclairage ; linéaire, connecteur d'angle 90° ou segment CURVE 90° ; avec profil de rail intégré pour fixation d'alimentation électrique et signal DALI ; surface anodisé ou thermolaquée ; montage flexible et sans outil de éléments grâce au support magnétique + verrouillage

Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118lm/W
L80 @ 50 000h
non DIM, DALI-2

Types



connector



corner



curve

Colours



standard



xal.com/colours



custom cut on
building site

Order options

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

● jet black RAL 9005

Options on request

CONNECTOR

T-connector

X-connector

INSTALLATION TRACK

acoustic soft ceilings



MOVE IT 25 S trimless



INSTALLATION TRACK

L (mm)

L (mm)		ORDER CODE
617	channel	050-721208
1217	channel	050-721408
2417	channel	050-721808
3622	channel	050-721908
cust. cut	channel (non DIM)	E83131.....8
cust. cut	channel (DALI-2)	E83141.....8
672x645	channel corner* 90°	050-721108
661x661	channel corner* ceiling to wall 90°	050-721118

*incl. electrical connector set

Accessories

END CAPS

TYPE

TYPE	ORDER CODE
end caps (pair)	050-721008

BLIND COVER

L (mm)

L (mm)	ORDER CODE
1217	050-7004008
2417	050-7008008
3622	050-7009008
custom cut	E83000.....8B

blind cover can be shortened as desired

CONNECTOR SET

TYPE

TYPE	ORDER CODE
linear connector (non DIM, DALI-2)	050-2031130
linear connector flexible	050-203210
mechanical linear connector (pair)	050-2011110

POWER FEEDER UNIT

TYPE

TYPE	ORDER CODE
non DIM 2×2,5mm ²	050-2020110
DALI-2 2×2,5 + 2×0,5mm ²	050-2020130

cable length 500 mm

Electrical accessories

see following pages



Order options

CONTROL	
non DIM	1
DALI-2	3

MATERIAL COLOUR	
● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	
● gold dust 260-M / jet black 9005 G	
● special colours*	X

*inside always in black

MATERIAL COLOUR ACCESSORIES	
○ traffic white RAL 9016	7
● jet black RAL 9005	8

MATERIAL COLOUR CABLE SUSPENSION	
chrome	0
black	8

Options on request

CONNECTOR	
T-connector	
X-connector	



MOVE IT 25 S surface / suspended



INSTALLATION TRACK / BLIND COVER

L (mm)		ORDER CODE
620	channel	050-73120
1220	channel	050-73140
2420	channel	050-73180
3625	channel	050-73190
cust. cut	channel (non DIM)	E83151
cust. cut	channel (DALI-2)	E83161
637x610	channel corner* 90°	050-73110
666x666	channel corner* ceiling to wall 90°	050-73111
*incl. electrical connector set		
1217	blind cover	050-7004008
2417	blind cover	050-7008008
3622	blind cover	050-7009008
cust. cut	blind cover	E83000

CURVE CONNECTOR

TYPE	ORDER CODE
mechanical & electrical R 300mm	050-731303
mechanical R 300mm	050-731311

Accessories

END CAPS

TYPE	ORDER CODE
end caps (pair)	050-731000

CONNECTOR SET

TYPE	ORDER CODE
mechanical linear conn. incl. 1500 mm cable susp.	050-201131
mechanical linear connector surface	050-2011410
mechanical & electrical linear connector	050-2031230

POWER FEEDER UNIT

TYPE	L (mm)	ORDER CODE
non DIM 2x2,5mm ²	2000	050-2022110
DALI-2 2x2,5 + 2x0,5mm ²	2000	050-2022130
non DIM 2x2,5mm ²	4000	050-2024110
DALI-2 2x2,5 + 2x0,5mm ²	4000	050-2024130

CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
ceiling fastener	10	050-204111
cable suspension	1500	005-215211
canopy		005-231171

*use every 1200 mm

Electrical accessories

see following pages

Order options

COLOUR TEMPERATURE

3000K

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● gold dust 260-M / jet black 9005 G
● special colours* X

*inside always in black

MATERIAL COLOUR

ACCESSORIES

○ traffic white RAL 9016 7
● jet black RAL 9005 8

MATERIAL COLOUR

CABLE SUSPENSION

chrome 0
black 8

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

2700K
4000K
tunable white 2700–6500K*
*DALI-2 DT8

CONNECTOR

T-connector
X-connector



MOVE IT 25 S suspended indirect



INSTALLATION TRACK INDIRECT

L (mm)	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
620	6.2W	648lm	050-74125
1220	15.3W	1810lm	050-74145
2420	33W	3890lm	050-74185
3625	51W	6000lm	050-74195
637x610 corner*	13.1W	1550lm	050-74110

incl. chrome cable suspension for L=1220/2420/3625 mm
no custom cut on building side; *incl. electrical connector set

1217	blind cover	050-7004008
2417	blind cover	050-7008008
3622	blind cover	050-7009008
cust. cut	blind cover	E83000 ···· 8B

Accessories

END CAPS



TYPE	ORDER CODE
end caps (pair)	050-731000

CONNECTOR SET



TYPE	ORDER CODE
mechanical linear conn. incl. 1500mm cable susp.	050-201131
mechanical & electrical linear connector	050-2031230

POWER FEEDER UNIT



TYPE	L (mm)	ORDER CODE
non DIM 2 × 2,5mm ²	2000	050-2022110
DALI-2 2 × 2,5 + 2 × 0,5mm ²	2000	050-2022130
non DIM 2 × 2,5mm ²	4000	050-2024110
DALI-2 2 × 2,5 + 2 × 0,5mm ²	4000	050-2024130

CABLE SUSPENSION / CANOPY



TYPE	L (mm)	ORDER CODE
cable suspension	1500	005-215211
canopy		005-231171

*use every 1200 mm

Electrical accessories

see following pages



Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118 lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types



connectors



Colours



MOVE IT 25 system

trimless / surface / suspended

EN Extruded aluminium profile with 28 mm width groove; for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5 mm ceiling thickness; or for wall/ ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; node connectors, up to 6 profile connection options; with power track profile for take off of supply voltage and DALI signal; surf. anod. or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking; sound absorbing accessories available

FR Profil extrudé en aluminium avec 28 mm de largeur de joint ; pour montage sans bord dans des plafonds en placoplâtre (murales ou au plafond) de 12,5 mm ; ou pour un montage en surface au mur ou au plafond ou pour un montage suspendu (suspension par câble, réglage de la hauteur sans outil, câble d'alimentation noir inclus) ; en option composants lumineux indirects pour une accentuation supplémentaire du plafond ; pour les systèmes d'éclairage ; linéaire, connecteur d'angle 90° ou segment CURVE 90° ; jonctions avec jusqu'à 6 options de raccordement ; avec profil de rail pour la captation de la tension d'alimentation et signal DALI; surf. anod. ou thermolaquée ; montage flexible et sans outil de éléments grâce au support magnétique + verrouillage ; accessoires doté de propriétés d'absorption acoustique



custom cut on building site



acoustic elements

Order options

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

● jet black RAL 9005

Options on request

CONNECTOR

T-connector
X-connector

INSTALLATION TRACK

acoustic soft ceilings



MOVE IT 25 trimless



INSTALLATION TRACK

L (mm)		ORDER CODE
617	channel	050-72020-8
1217	channel	050-72040-8
2417	channel	050-72080-8
3622	channel	050-72090-8
cust. cut	channel (non DIM)	E83031-8
cust. cut	channel (DALI-2)	E83041-8
672x645	channel corner* 90°	050-72010-8
661x661	channel corner* ceiling to wall 90°	050-72011-8

*incl. electrical connector set

Accessories

END CAPS

TYPE	ORDER CODE
end caps (pair)	050-72000-8



BLIND COVER

L (mm)	ORDER CODE
1217	050-70040-8
2417	050-70080-8
3622	050-70090-8
custom cut	E83000-8B



blind cover can be shortened as desired

CONNECTOR SET

TYPE	ORDER CODE
linear connector (non DIM, DALI-2)	050-20311-30
linear connector flexible	050-20321-0
mechanical linear connector (pair)	050-20111-10



POWER FEEDER UNIT

TYPE	ORDER CODE
non DIM 2x2,5mm ²	050-20201-10
DALI-2 2x2,5 + 2x0,5mm ²	050-20201-30



cable length 500 mm

Electrical accessories

see following pages

Order options

CONTROL	◆
non DIM	1
DALI-2	3

MATERIAL COLOUR	■
INSTALLATION TRACK	■
● jet black RAL 9005	8
○ traffic white 9016 / jet black 9005 P	
● gold dust 260-M / jet black 9005 G	
● special colours*	X

*inside always in black

MATERIAL COLOUR	■
NODE CONNECTOR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours	X



MATERIAL COLOUR	■
NODE LTX / END CAP	■
● jet black RAL 9005	8
○ traffic white 9016 / jet black 9005 P	
● special colours	X

MATERIAL COLOUR	■
ACCESSORIES	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

MATERIAL COLOUR	□
CABLE SUSPENSION	□
chrome	0
black	8

NODE CONNECTOR	⊕
MOUNTING TYPE	⊕
surface*	1
1500 mm cable susp. chrome	3
1500 mm cable susp. black	4

*only for L/T/X



MOVE IT 25 surface / suspended



INSTALLATION TRACK / BLIND COVER

L (mm)		ORDER CODE
620	channel	050-73020
1220	channel	050-73040
2420	channel	050-73080
3625	channel	050-73090
cust. cut	channel (non DIM)	E83051
cust. cut	channel (DALI-2)	E83061
637x610	channel corner* 90°	050-73010
666x666	channel corner* ceiling to wall 90°	050-73011
*incl. electrical connector set		
1217	blind cover	050-7004008
2417	blind cover	050-7008008
3622	blind cover	050-7009008
cust. cut	blind cover	E83000 ···· 8B

CURVE CONNECTOR

TYPE	ORDER CODE
mechanical & electrical R 300 mm	050-730303
mechanical R 300 mm	050-730311

Accessories

END CAPS

TYPE	ORDER CODE
end caps (pair)	050-730000

FLEX NODE CONNECTOR

TYPE	ORDER CODE
FLEX NODE surface mounted	050-203333
FLEX NODE surface mounted incl. feeder	050-202243
FLEX NODE cable suspension 1500 mm	050-203318
FLEX NODE cable susp. 1500 mm incl. feeder	050-202228
NODE end cap* incl. electrical connector	050-730010

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

TYPE	ORDER CODE
mechanical linear conn. incl. 1500 mm cable susp.	050-201131
mechanical linear connector surface	050-201141
mechanical & electrical linear connector	050-203123

POWER FEEDER UNIT

TYPE	L (mm)	ORDER CODE
non DIM 2×2,5 mm ²	2000	050-2022110
DALI-2 2×2,5 + 2×0,5 mm ²	2000	050-2022130
non DIM 2×2,5 mm ²	4000	050-2024110
DALI-2 2×2,5 + 2×0,5 mm ²	4000	050-2024130

CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
ceiling fastener	10	050-204111
cable susp. (use very 1200 mm)	1500	005-215211
canopy		005-231171

Electrical accessories

see following pages

Acoustic elements

see following pages

Order options

COLOUR TEMPERATURE

3000K

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR INSTALLATION TRACK

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● gold dust 260-M / jet black 9005 G
● special colours* X

*inside always in black

MATERIAL COLOUR NODE CONNECTOR

○ traffic white RAL 9016 7
● jet black RAL 9005 8
● special colours X

MATERIAL COLOUR NODE LTX/END CAP

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● special colours X

MATERIAL COLOUR ACCESSORIES

○ traffic white RAL 9016 7
● jet black RAL 9005 8

MATERIAL COLOUR CABLE SUSPENSION

chrome 0
black 8

NODE CONNECTOR MOUNTING TYPE

surface* 1
1500 mm cable susp. chrome 3
1500 mm cable susp. black 4

*only for L/T/X

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

2700 K
4000 K
tunable white 2700–6500 K*

*DALI-2 DT8



MOVE IT 25 suspended indirect



INSTALLATION TRACK INDIRECT

L (mm)	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
620	6.2W	648lm	050-74025
1220	15.3W	1810lm	050-74045
2420	33W	3890lm	050-74085
3625	51W	6000lm	050-74095
637x610 corner*	13.1W	1550lm	050-74010

incl. chrome cable suspension for L=1220/2420/3625 mm
no custom cut on building side; *incl. electrical connector set

1217	blind cover	050-7004008
2417	blind cover	050-7008008
3622	blind cover	050-7009008
cust. cut	blind cover	E83000 ···· 8B

Accessories

END CAPS

TYPE	ORDER CODE
end caps (pair)	050-730000

FLEX NODE CONNECTOR

TYPE	ORDER CODE
FLEX NODE cable suspension 1500 mm	050-20331
FLEX NODE cable susp. 1500mm incl. feeder	050-20222
FLEX NODE end cap* incl. electrical connector	050-730010

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

TYPE	ORDER CODE
mechanical linear conn. incl. 1500 mm cable susp.	050-201131
mechanical & electrical linear connector	050-2031230

POWER FEEDER UNIT

TYPE	L (mm)	ORDER CODE
non DIM 2 × 2,5 mm ²	2000	050-2022110
DALI-2 2 × 2,5 + 2 × 0,5 mm ²	2000	050-2022130
non DIM 2 × 2,5 mm ²	4000	050-2024110
DALI-2 2 × 2,5 + 2 × 0,5 mm ²	4000	050-2024130

CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
cable suspension*	1500	005-215211
canopy		005-231171

*use every 1200 mm



Electrical accessories

see following pages

Acoustic elements

see following pages

LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white/black

Order options

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8



Electrical accessories

POWER SUPPLY INTRACK supply 220-240 V AC, 48 V, 50-60 Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
100 W PC II η 92 %		intrack	403-26-46	050-2071038
150 W PC II η 92 %		intrack	403-26-46	050-2071138

incl. feeder cable 2000 mm; ENEC approved; DALI-2 SELV device integrated

POWER SUPPLY SURFACE supply 220-240 V AC, 48 V, 50-60 Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
60 W PC II η 88 %		surface	305-144-54	050-20551
100 W PC II η 92 %		surface	455-104-40	050-20554
150 W PC II η 92 %		surface	455-104-40	050-20552
250 W PC II η 93 %		surface	455-104-40	050-20555
320 W PC I η 94 %		surface	305-144-54	050-20553

ENEC approved; DALI-2 SELV device integrated

POWER SUPPLY EXTERNAL supply 220-240 V AC, 48 V, 50-60 Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
60 W PC II η 88 %		external	163-43-32	002-62133
100 W PC II η 92 %		external	350-30-18	002-62134
150 W PC II η 92 %		external	350-30-18	002-62135
250 W PC II η 93 %		external	400-40-22	002-62139
320 W PC I η 94 %		external	252-90-44	002-60320

ENEC approved

POWER SUPPLY BASIC 48 V

220-240 V | 50-60 Hz | PC II | Lifetime @ 120 W, 45° ambient temp. cascable max. 3 devices

TYPE	EFFICIENCY / LIFETIME	W-H-D (mm)	ORDER CODE
160 W η 94.5 % / > 100.000 h		72-90-63	005-6520210

DIN RAIL POWER SUPPLY PRO 48 V

220-240 V | 50-60 Hz | PC I | MTBF @ 55° ambient temperature cascable max. 5 devices (240 W) or 3 devices (480 W)

TYPE	EFFICIENCY / MTBF	W-H-D (mm)	ORDER CODE
240 W η 92 % / > 400.000 h		60-125-100	005-6220110
480 W η 93 % / > 350.000 h		120-125-100	005-6220210

DALI-2 SELV DEVICE

TYPE	L-W-H (mm)	ORDER CODE
control unit	213-37-25	050-2061130

necessary to create DALI-2 SELV signal; DALI power supply integrated

DALI SENSOR

TYPE	L-W-H (mm)	ORDER CODE
ESSENTIAL sensor (brightness & presence)	125-28-45	050-2063178

WIRELESS TO DALI-2 CONTROL DEVICE

TYPE	L-W-H (mm)	ORDER CODE
Casambi	111-25-45	050-2065230

DALI-2 SELV device required

WIRELESS TO DALI-2 REPEATER

TYPE	L-W-H (mm)	ORDER CODE
Casambi	111-25-45	050-2066230

MIDDLE FEED

TYPE	ORDER CODE
DALI-2 2 × 2,5 + 2 × 0,5 mm ² cable length 2000 mm	050-2038130

Blique by Nobis
Stockholm, SE –
by Wingårdhs





JUST

spotlight inset 25/25S

Quickinfo

2700K, 3000K, 4000K, TW, CWD
 CRI ≥ 90, 2 SDCM
 non DIM, DALI-2

L95 @ 50 000h
 JUST 32 focus up to 47lm/W

L80 @ 50 000h
 JUST 45 up to 72lm/W

L90 @ 50 000h
 JUST 55 up to 88lm/W

Types



Colours



Light distributions

JUST 32 focus



JUST 45



JUST 55



Order options

COLOUR TEMPERATURE	
2700K	4
3000K	5
4000K	6
colour warm dim. 2000–3000K*	
tunable white 1800–3000K**	
tunable white 2700–6500K**	

*DALI-2 **DALI-2 DT8

CONTROL	
non DIM	1
DALI-2	3

MATERIAL COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8
🌈 special colours	X

BEAM ANGLE JUST 45	
medium 23°	M
flood 44°	F

BEAM ANGLE JUST 55	
spot 16°	S
medium 23°	M
flood 37°	F

Options on request

OPTICAL ACCESSORIES

elliptical sculpture foil
 snoot
 colour filter (red, blue, green, etc.)
 only for JUST 32 focus



JUST 32 focus 17–43°



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.3W	393lm	050-01111

JUST 45



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.1W super spot 8°	297lm	050-01311
11W	788lm	050-01311
12W CWD 2000–3000K	430lm	050-01311E3
11W TW 1800–3000K	555lm	050-01311L3
11W TW 2700–6500K	683lm	050-01311D3

JUST 55



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
16.4W	1430lm	050-01433
25.4W	2010lm	050-01423

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
JUST 32 focus	30·4	007-1965178
JUST 45	42·3	007-1965188
JUST 55	50·3	007-1965598

OVAL LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 45	42·3	007-1965880
BO 55	50·3	007-1965890

SOFT LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 45	42·3	007-1965980
BO 55	50·3	007-1965990

WALLWASHER LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 45	42·3	007-1965780
BO 55	50·3	007-1965790

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥90, colour white, lens flood 2700K -5%, 4000K +5%



MOVE IT 25 SYSTEM



Quickinfo

2700 K, 3000 K, TW
CRI ≥ 90, 3 SDCM
up to 123lm/W
L90 @ 50 000h
non DIM, DALI-2

Types



Colour



Light distribution



opal



reddot award 2019
winner



DESIGN
AWARD
2019

PIVOT

graphic light inset 25/25S



tunable white
1800–4000K



CRI ≥ 98
XPECTRUM

Order options

COLOUR TEMPERATURE ◆◆

2700 K	4
3000 K	5
tunable white 1800–4000 K*	L

*DALI-2 DT8

CONTROL ◆

non DIM	1
DALI-2	3

MATERIAL COLOUR

● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX
CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE
4000 K

MATERIAL COLOUR
○ traffic white RAL 9016



LIGHT INSET 25S



PIVOT

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
10.6 W	2700 K	1190 lm	610	0 5 0 - 1 3 1 2 ◆◆ 8 0
	3000 K	1260 lm		
15.9 W	2700 K	1780 lm	910	0 5 0 - 1 3 1 3 ◆◆ 8 0
	3000 K	1890 lm		
21.2 W	2700 K	2380 lm	1210	0 5 0 - 1 3 1 4 ◆◆ 8 0
	3000 K	2530 lm		
26.4 W	2700 K	2970 lm	1510	0 5 0 - 1 3 1 5 ◆◆ 8 0
	3000 K	3160 lm		
32 W	2700 K	3570 lm	1810	0 5 0 - 1 3 1 6 ◆◆ 8 0
	3000 K	3790 lm		



PIVOT SUSPENDED

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
10.6 W	2700 K	1190 lm	610	0 5 0 - 0 3 2 2 ◆◆ 8 0
	3000 K	1260 lm		
15.9 W	2700 K	1780 lm	910	0 5 0 - 0 3 2 3 ◆◆ 8 0
	3000 K	1890 lm		
21.2 W	2700 K	2380 lm	1210	0 5 0 - 0 3 2 4 ◆◆ 8 0
	3000 K	2530 lm		
26.4 W	2700 K	2970 lm	1510	0 5 0 - 0 3 2 5 ◆◆ 8 0
	3000 K	3160 lm		



LIGHT INSET 25



PIVOT

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
10.6 W	2700 K	1190 lm	610	0 5 0 - 0 3 1 2 ◆◆ 8 0
	3000 K	1260 lm		
15.9 W	2700 K	1780 lm	910	0 5 0 - 0 3 1 3 ◆◆ 8 0
	3000 K	1890 lm		
21.2 W	2700 K	2380 lm	1210	0 5 0 - 0 3 1 4 ◆◆ 8 0
	3000 K	2530 lm		
26.4 W	2700 K	2970 lm	1510	0 5 0 - 0 3 1 5 ◆◆ 8 0
	3000 K	3160 lm		
32 W	2700 K	3570 lm	1810	0 5 0 - 0 3 1 6 ◆◆ 8 0
	3000 K	3790 lm		



PIVOT SUSPENDED

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
10.6 W	2700 K	1190 lm	610	0 5 0 - 0 3 2 2 ◆◆ 8 0
	3000 K	1260 lm		
15.9 W	2700 K	1780 lm	910	0 5 0 - 0 3 2 3 ◆◆ 8 0
	3000 K	1890 lm		
21.2 W	2700 K	2380 lm	1210	0 5 0 - 0 3 2 4 ◆◆ 8 0
	3000 K	2530 lm		
26.4 W	2700 K	2970 lm	1510	0 5 0 - 0 3 2 5 ◆◆ 8 0
	3000 K	3160 lm		

LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



FLEXTRACK

system extension 25/25S

EN Thin extruded aluminium profile with 31mm height and 28mm width groove; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; for installation in two MOVE IT 25 or 25 S profiles; profile can be installed and moved without tools by means of magnetic holders + locking; mount 360° rotatable and freely slidable on one end; light insets can be installed flexibly and without tools by means of magnetic holders+locking

FR Profil extrudé en aluminium plat avec 31mm de hauteur et 28mm de largeur de joint ; avec profil de rail intégré pour fixation d'alimentation électrique et signal DALI ; surface anodisé ou thermolaquée ; à encastrer dans deux profils MOVE IT 25 ou MOVE IT 25 S ; l'profilé peut être inséré et déplacé sans outil grâce au support magnétique + verrouillage ; fixation rotatif à 360° et coulissante à volonté sur une extrémité ; montage flexible et sans outil de éléments lumineux grâce au support magnétique + verrouillage

Quickinfo

non DIM, DALI-2

Types



Colours



Order options

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	
● gold dust 260-M / jet black 9005 G	
● special colours*	X

*inside always in black

MOVE IT 25 S



FLEXTRACK

L (mm)

620
920
1220
1520
1820

ORDER CODE

050-75120
050-75130
050-75140
050-75150
050-75160

MOVE IT 25



FLEXTRACK

L (mm)

620
920
1220
1520
1820

ORDER CODE

050-75020
050-75030
050-75040
050-75050
050-75060



Quickinfo

2700 K, 3000 K, 4000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 84 lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distributions



ARY rod
 decorative inset 25/25S



Order options

CABLE SUSPENSION

1500 mm	5
2000 mm with hook*	6

*one ring included

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6
tunable white 2200–4000 K*	

*DALI-2 DT8

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours	X

ACCESSORY COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

medium 25°	M
flood 44°	F



ARY rod



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	2700 K	1050 lm	050-0 3 2 1
	3000 K	1100 lm	
	4000 K	1180 lm	
5.4 W TW	2200–4000 K	284 lm	050-0 3 2 1 D 3

ARY rod adjustable



SPOTLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	2700 K	1050 lm	050-0 3 3 1
	3000 K	1100 lm	
	4000 K	1180 lm	
5.4 W TW	2200–4000 K	284 lm	050-0 3 3 1 D 3



Mounting accessories

RING track mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25 S	50-70	050-151011
MOVE IT 25	50-91	050-051011



RING ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25S/25	50-88	050-051021





Quickinfo

2700 K, 3000 K, 4000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 84 lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distributions



ARY cable
 decorative inset 25/25S





Quickinfo

2700 K, 3000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 75 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types



Colours



Light distributions



TULA

decorative inset 25/25S



free positioning by
ring and hook



tunable white
2200 – 4000 K

Order options

HOUSING HEIGHT

300 mm	0
500 mm	1

CABLE SUSPENSION

1500 mm	7
2000 mm with hook*	8

*one ring included

COLOUR TEMPERATURE

2700 K	4
3000 K	5
tunable white 2200 – 4000 K*	

*DALI-2 DT8

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

∅ chrome	4
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours	X

ACCESSORY COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

medium 25°	M
flood 44°	F

Options on request

COLOUR TEMPERATURE

4000 K



TULA nano suspended



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11W	2700K	642lm	050-L 11 1
	3000K	688lm	



TULA micro suspended



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14W	2700K	998lm	050-L 15 1
	3000K	1048lm	
5.4W	2200 – 4000K	254lm	050-L 15 D 3

Mounting accessories

RING track mounted



TYPE	∅-H (mm)	ORDER CODE
MOVE IT 25 S	50-70	050-151011
MOVE IT 25	50-91	050-051011

RING ceiling mounted



TYPE	∅-H (mm)	ORDER CODE
MOVE IT 25S/25	50-88	050-051021



Quickinfo

2700 K, 3000 K
CRI \geq 90, 3 SDCM
up to 55 lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types



Colours



Light distribution



Order options

CABLE SUSPENSION

1500 mm	5
2000 mm with hook*	6

*one ring included

COLOUR TEMPERATURE

2700 K	4
3000 K	5

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8
● special colours	X

ACCESSORY COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8



PAL suspended



DOWNLIGHT

INS. POWER	COLOUR TEMP.	LUM. FLUX	Ø (mm)	ORDER CODE
9.1W	2700K	472lm	80	050-1 8 1 1
	3000K	498lm		
9.1W	2700K	472lm	120	050-1 8 1 3
	3000K	498lm		

Mounting accessories

RING track mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25 S	50-70	050-151011
MOVE IT 25	50-91	050-051011



RING ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25S/25	50-88	050-051021



INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white, glass



Quickinfo

2700 K
CRI ≥ 95, 3 SDCM
up to 72 lm/W
L90 @ 50 000h
non DIM, DALI-2

Types



Colours



wästberg w201 Extra small pendant

Design by Claesson Koivisto Rune

Order options

CABLE SUSPENSION	
3000 mm	5
3000 mm with hook	6

COLOUR TEMPERATURE	
2700 K	

CONTROL	
non DIM	1
DALI-2	3

MATERIAL COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8

ACCESSORY COLOUR	
○ pure white RAL 9010	7
● jet black RAL 9005	8



w201 Extra small pendant s1



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.9W	2700 K	544lm	050-04814



w201 Extra small pendant s2



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.9W	2700 K	572lm	050-04824



w201 Extra small pendant s3



DOWNLIGHT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.9W	2700 K	572lm	050-04834

Mounting accessories



RING track mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25 S	50-70	050-151011
MOVE IT 25	50-91	050-051011



RING ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
MOVE IT 25S/25	50-88	050-051021

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white



SPOT LINE / OPAL

linear inset 25

Quickinfo

2700 K, 3000 K, TW (opal)
 CRI ≥ 90, 3 SDCM
 SPOT LINE up to 80 lm/W
 OPAL up to 101 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types

MOVE IT 25

SPOT LINE



OPAL



Light distributions



tunable white
 1800–4000 K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
tunable white 1800–4000 K*	L

*only available for opal high performance inset | DALI-2 DT8

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

4000 K



LIGHT INSET 25



SPOT LINE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
3 × 1.4 W	2700 K	309lm	155	0 5 0 - 0 2 2 0 :: 8 M
	3000 K	336lm		
6 × 1.4 W	2700 K	618lm	305	0 5 0 - 0 2 2 1 :: 8 M
	3000 K	672lm		
12 × 1.4 W	2700 K	1240lm	605	0 5 0 - 0 2 2 2 :: 8 M
	3000 K	1340lm		



OPAL HIGH PERFORMANCE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.3 W	2700 K	451lm	305	0 5 0 - 0 2 1 1 :: 8 H
	3000 K	484lm		
10.6 W	2700 K	902lm	605	0 5 0 - 0 2 1 2 :: 8 H
	3000 K	968lm		
21.3 W	2700 K	1800lm	1205	0 5 0 - 0 2 1 4 :: 8 H
	3000 K	1940lm		
43 W	2700 K	3610lm	2405	0 5 0 - 0 2 1 8 :: 8 H
	3000 K	3870lm		



LIGHT INSET 25 S



OPAL HIGH PERFORMANCE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.3 W	2700 K	402lm	305	0 5 0 - 1 2 1 1 :: 8 H
	3000 K	432lm		
10.6 W	2700 K	805lm	605	0 5 0 - 1 2 1 2 :: 8 H
	3000 K	864lm		
21.3 W	2700 K	1610lm	1205	0 5 0 - 1 2 1 4 :: 8 H
	3000 K	1730lm		
43 W	2700 K	3220lm	2405	0 5 0 - 1 2 1 8 :: 8 H
	3000 K	3460lm		

canyon solution for MOVE IT 25

Light distribution



spot line

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



WALLWASHER

linear inset 25/25S

Quickinfo

2700 K, 3000 K
 CRI ≥ 90, 3 SDCM
 WALLWASHER up to 81lm/W
 WW flush up to 82lm/W
 L80 @ 50 000 h
 non DIM, DALI-2


Types

MOVE IT 25

WALLWASHER




WALLWASHER flush



MOVE IT 25 S

WALLWASHER flush



Light distribution



wall washer



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	☼☼
2700 K	4
3000 K	5

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3

MATERIAL COLOUR	
● jet black RAL 9005	

Options on request

COLOUR RENDERING INDEX	
CRI ≥ 98 XPECTRUM	

COLOUR TEMPERATURE	
4000 K	



LIGHT INSET 25



WALLWASHER

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13 W	2700 K	983lm	450	050-0232 ☼☼ 38 A
	3000 K	1050lm		



WALLWASHER FLUSH

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.6 W	2700 K	415lm	305	050-0211 ☼☼ 8 A
	3000 K	454lm		
11.2 W	2700 K	829lm	605	050-0212 ☼☼ 8 A
	3000 K	908lm		
22.3 W	2700 K	1660lm	1205	050-0214 ☼☼ 8 A
	3000 K	1820lm		
45 W	2700 K	3320lm	2405	050-0218 ☼☼ 8 A
	3000 K	3630lm		

Optical accessories

ANTI-GLARE GRID

TYPE	L-W (mm)	ORDER CODE
WALLWASHER FLUSH	303-25	050-0230918

cluster solution to create anti-glare grid for all lengths



LIGHT INSET 25 S



WALLWASHER FLUSH

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.6 W	2700 K	415lm	305	050-1211 ☼☼ 8 A
	3000 K	454lm		
11.2 W	2700 K	829lm	605	050-1212 ☼☼ 8 A
	3000 K	908lm		
22.3 W	2700 K	1660lm	1205	050-1214 ☼☼ 8 A
	3000 K	1820lm		
45 W	2700 K	3320lm	2405	050-1218 ☼☼ 8 A
	3000 K	3630lm		

Light distributions



wallwasher



wallwasher flush

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



MOVE IT 25 SYSTEM

WALL GRAZER / BATWING

linear inset 25S

Quickinfo

2700 K, 3000 K
CRI \geq 90, 3 SDCM
WALL GRAZER up to 107lm/W
BATWING up to 104lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types

MOVE IT 25 S

WALL GRAZER / BATWING



Light distributions



CRI \geq 98
XPECTRUM

Order options

COLOUR TEMPERATURE	••
2700 K	4
3000 K	5

CONTROL	◆
non DIM	1
DALI-2	3

MATERIAL COLOUR
● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX
CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE
4000 K



LIGHT INSET 25 S



WALL GRAZER

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.3 W	2700 K	525lm	305	0 5 0 - 1 2 1 1 :: 8 S
	3000 K	564lm		
10.6 W	2700 K	1050lm	605	0 5 0 - 1 2 1 2 :: 8 S
	3000 K	1130lm		
21.3 W	2700 K	2100lm	1205	0 5 0 - 1 2 1 4 :: 8 S
	3000 K	2260lm		
43 W	2700 K	4200lm	2405	0 5 0 - 1 2 1 8 :: 8 S
	3000 K	4510lm		



BATWING

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.3 W	2700 K	512lm	305	0 5 0 - 1 2 1 1 :: 8 B
	3000 K	550lm		
10.6 W	2700 K	1020lm	605	0 5 0 - 1 2 1 2 :: 8 B
	3000 K	1100lm		
21.3 W	2700 K	2050lm	1205	0 5 0 - 1 2 1 4 :: 8 B
	3000 K	2200lm		
43 W	2700 K	4100lm	2405	0 5 0 - 1 2 1 8 :: 8 B
	3000 K	4400lm		

Light distributions



wall grazer



batwing

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

MOVE IT 25 system

acoustic elements

EN Acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties; different versions: choice of square, rectangular or triangular design; high quality visual and tactile surface with embossed pattern; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools

FR Élément acoustique en feutre PET recyclé, autoportant, haute qualité, doué de propriétés insonorisantes ; diverses variantes : forme au choix carrée, rectangulaire ou triangulaire ; surface de haute qualité optique et tactile avec motif gaufré ; inclusions de fibres étrangères possibles ; absorption du bruit direct et du bruit réfléchi par le plafond ; pour de meilleures performances acoustiques ; à insérer dans le système suspendu MOVE IT 25 composé de jonctions et profils disponibles ; possibilité d'insertion ultérieure dans un MOVE IT suspended system déjà en place ; montage sans outil

Quickinfo

PET felt

from recycled material

available as B-s1, d0

Types



Colours



easy
mounting



sound absorption
by recycled PET

Order options

MATERIAL COLOUR		<input checked="" type="checkbox"/>
<input type="radio"/> white		W
<input type="radio"/> marble grey		D
<input type="radio"/> black		L

Options on request

MATERIAL COLOUR
 painted in custom colour _____

DIMENSIONS
 cut in custom dimensions _____



MOVE IT 25 acoustic suspended

PET
felt

ACOUSTIC ELEMENT

TYPE	L-W-H (mm)	ORDER CODE
square grid inlay	1235·1235·25	050-231121 <input checked="" type="checkbox"/>
half grid inlay	635·1235·25	050-231221 <input checked="" type="checkbox"/>
double grid inlay	2435·1235·25	050-231321 <input checked="" type="checkbox"/>
triangle inlay	1195·1035·25	050-231421 <input checked="" type="checkbox"/>

mounting only in MOVE IT 25 system with NODE connector + track 1220 mm, 620 mm or 2420 mm

ACOUSTIC EXAMPLES

