

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-0711417F



Projet / Type _____

Notes _____

Quantité / Date _____



Général

Plafond , Suspendu _____

blanc , RAL9016 ¹ _____

IP20 _____

667 lm _____

LED

2700 K _____

CRI ≥ 90 _____

MacAdam initial ≤ 3 SDCM _____

R_g: 99 , R_f: 91 , R_{f(1-15)}: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optique

flood _____

angle de faisceau 30° _____

Electrique

non DIM _____

12.1 W _____

CP3 _____

55 lm/W _____

Physique

diamètre 26 mm _____


hauteur 300 mm _____

0.25 kg _____

1500 mm _____

¹ Code RAL

Répartition de la lumière



flood 30°

h (m)	EO° (lx)	ø (m)
1	1960	0.53
2	490	1.07
3	220	1.60
4	120	2.13
5	80	2.66

Dessin de fabrication



Notice de montage



Calculateur d'éclairage



TULA nano suspended

MOVE IT 25 / 25 S / 45

050-0711417F



Projet / Type

Notes

Quantité / Date

Accessoires de montage

RING TRACK MOUNTED

COULEUR	Ø (MM)	NUMÉRO(S) ARTICLE(S)
blanc signalisation	50	050-051017
Noir profond	50	050-051018



RING CEILING MOUNTED

COULEUR	Ø (MM)	NUMÉRO(S) ARTICLE(S)
blanc signalisation	50	050-0510217
Noir profond	50	050-0510218

